

Date Printed: 2/23/2023

Safety Data Sheet

Product: 3538SP3000

1. Identification	
Product Information:	3538SP3000
Product Name:	SEAJET 038 TAISHO BRIGHT RED
Recommended Use:	ANTI-FOULING PAINT
Supplied by:	CMP Coatings, Inc. 1610 Engineers Rd. Belle Chasse, LA 70037
Emergency Telephone: Safety Data Sheet Coordinator:	Chemtrec 24 Hour Emergency Hotline: 800-424-9300 SDS@cmpusa.com

2. Hazards Identification

EMERGENCY OVERVIEW: Extremely Flammable!Eye irritant.

GHS Classification

Acute Tox. 2 Inhalation, Acute Tox. 2 Oral, Carc. 2, Eye Dam. 1, Flam. Liq. 2, Repr. 1A, STOT RE 2

Symbol(s) of Product



Signal Word Danger

Possible Hazards

57% of the mixture consists of ingredients of unknown acute toxicity

GHS HAZARD STATEMENTS

GHS HAZARD STATEMENTS			
Acute Toxicity, Inhalation, category 2	H330	Fatal if inhaled.	
Acute Toxicity, Oral, category 2	H300	Fatal if swallowed.	
Carcinogenicity, category 2	H351	Suspected of causing cancer. Classified as Category 2 based on limited evidence on human and/or animal studies. Mixtures with concentrations of suspected carcinogens ingredients at concentration present between 0.1% and 1.0% labelling the SDS will be optional depending on authorities. If Category 2 carcinogenic present at a concentration of 1% or above labelling the SDS will be expected. Routes of exposure are dependant on ingredient form.	
Flammable Liquid, category 2	H225	Highly flammable liquid and vapour.	
Reproductive Toxicity, category 1A	H360	May damage fertility or the unborn child. Classified Category 1A known human reproductive toxicant Category 1B presumed human reproductive toxicant. Irreversible effects such as structural malfunctions, embryo/foetal lethality, post natal functional deficiencies.	
STOT, repeated exposure, category 2	H373	May cause damage to organs (hematopoietic system [blood forming], blood, bone marrow, immune system) through prolonged or repeated exposure.	
Serious Eye Damage, category 1	H318	Causes serious eye damage.	
GHS LABEL PRECAUTIONARY STATE	MENTS		
P201	Obtain special instructions before use.		
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.		
P260	Do not brea	the dust/fume/gas/mist/vapours/spray.	

P264	Wash thoroughly after handling.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P281	Use personal protective equipment as required.
P284	[In case of inadequate ventilation] wear respiratory protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P330	Rinse mouth.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
GHS SDS PRECAUTIONARY STATEM	ENTS
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting// equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P270	Do no eat, drink or smoke when using this product.

3. Composition/Information on Ingredients

<u>Chemical Name</u>	CAS-No.	Wt. % GHS Symbols	GHS Statements
ZINC OXIDE	1314-13-2	10-25 No Information	No Information
BENZENE,1-CHLORO-4 (TRIFLUOROMETHYL)	98-56-6	10-25 GHS07-GHS08	H336-373
1-HYDROXYPYRIDINE-2-THIONE ZINC SALT	13463-41-7	10-25 GHS05-GHS06	H301-318-331
XYLENE MIXTURE OF ISOMERS	1330-20-7	2.5-10 GHS02-GHS07	H226-312-315-332
1-METHOXY-2-PROPANOL	107-98-2	2.5-10 GHS02-GHS07-	H226-336-360
		GHS08	
ETHYL BENZENE	100-41-4	2.5-10 GHS07-GHS08	H304-332-351-373
TERT-BUTYL ACETATE	540-88-5	2.5-10 No Information	No Information
4-BROMO-2-(4-CHLOROPHENYL)-5-	122454-29-9	2.5-10 GHS06-GHS08	H300-311-330-372
(TRIFLUOROMETHYL)-1H-PYRROLE-3-			
CARBONITRILE			

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

4. First-aid Measures



FIRST AID - INHALATION: If inhaled, remove to fresh air. Administer oxygen if necessary. Consult a physician if symptoms persist or exposure was severe.

FIRST AID - SKIN CONTACT: In case of contact, wash skin immediately with soap and water. Launder clothing before reuse. Destroy contaminated leather articles.

FIRST AID - EYE CONTACT: If material gets into eyes, flush with water immediately for 15 minutes. Consult a physician.

FIRST AID - INGESTION: If ingested, DO NOT induce vomiting. If conscious, drink 8-10 oz. of water promptly. Call a physician immediately.

5. Fire-fighting Measures

UNUSUAL FIRE AND EXPLOSION HAZARDS: Flammable liquid. Vapors can form an ignitable mixture with air. Vapors can flow along surfaces to a distant ignition source and flash back.

SPECIAL FIREFIGHTING PROCEDURES: Use a self-contained breathing apparatus with full facepiece operated in pressure demand or other positive pressure mode. Flammable. Cool fire-exposed containers using water spray.

EXTINGUISHING MEDIA: Alcohol Foam, Carbon Dioxide, Dry Chemical, Foam, Water Fog

6. Accidental Release Measures

ENVIRONMENTAL PRECAUTIONS: Contain any spills immediately and dike area to prevent spreading. Package material and dispose of as hazardous waste.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Dike to prevent entering any sewer or waterway. Transfer liquid to a holding container. Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust. Remove all sources of ignition, ventilate area and remove with inert absorbent and non-sparking tools. Dispose of according to local, state, and federal regulations. Do not incinerate closed containers. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Ventilate area, isolate spilled material, and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

7. Handling and Storage



HANDLING: Flammable liquid. Avoid heat, sparks and open flames. Avoid breathing vapor and contact with eyes, skin and clothing. Hazardous residue may remain in emptied container. Do not reuse empty containers without commercial cleaning or reconditioning. Material will accumulate static charges which may cause an electrical spark (ignition source). Use proper grounding procedures.

STORAGE: Keep container closed when not in use.

8. Exposure Controls/Personal Protection

Ingredients with Occupational Exposu	re Limits ACGIH TLV-TWA	ACGIH-TLV STEL	<u>OSHA PEL-TWA</u>	OSHA PEL-CEILING
ZINC OXIDE	N.E.	N.E.	5 mg/m3 (dust; respirable)	N.E.
BENZENE,1-CHLORO-4 (TRIFLUOROMETHYL)	N.E.	N.E.	N.E.	N.E.
1-HYDROXYPYRIDINÉ-2-THIONE ZINC SALT	N.E.	N.E.	N.E.	N.E.
XYLENE MIXTURE OF ISOMERS	100 ppm	150 ppm	100 ppm	N.E.
1-METHOXY-2-PROPANOL	50 ppm	100 ppm	N.E.	N.E.
ETHYL BENZENE	20 ppm	125 ppm	100 ppm	N.E.
TERT-BUTYL ACETATE	200 ppm	N.E.	200 ppm	N.E.
4-BROMO-2-(4-CHLOROPHENYL)-5-	N.E.	N.E.	0.040 mg/m3	N.E.
(TRIFLUOROMETHYL)-1H-PYRROLE-3-				
CARBONITRILE				

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation Sk = Skin Sensitizer N.E. = Not Established

Personal Protection



RESPIRATORY PROTECTION: Respirator use is not expected to be necessary under normal conditions of handling. In emergency situations, use of a NIOSH-approved respirator may be required. When concentrations exceed the exposure limits specified, use of a NIOSH-approved dust, mist and fume respirator is recommended. Where the protection factor of the respirator may be exceeded, use of a full facepiece, supplied air, or Self Contained Breathing Apparatus (SCBA) may be necessary.



SKIN PROTECTION: Chemical-resistant gloves may be required for individuals with sensitive skin.



EYE PROTECTION: Ensure that eyewash stations and safety showers are close to the workstation location. Chemical resistant goggles must be worn.



OTHER PROTECTIVE EQUIPMENT: Use personal protective equipment as necessary. Safety shower and eyewash station should be located in immediate work area.



HYGIENIC PRACTICES: Contaminated clothing should be changed and washed before reuse. Eating, drinking and smoking in immediate work area should be prohibited. Keep away from food, drink and animal feeding stuffs.

9. Physical and Chemical Properties

Appearance: Odor: Density, g/cm3: Freeze Point, °F: Solubility in Water: Decomposition temperature, °F	Paint Solvent 1.518 No Information Insoluble Not Measured	Physical State: Odor Threshold: pH: Viscosity: Partition Coefficient, n-octanol/ water:	Liquid Not Established Not Applicable No Information Not Measured
Boiling Range, °F:	149 - 284	Explosive Limits, %:	0.9 - 10.5
Combustibility:	Supports Combustion	Flash Point, °F:	67
Evaporation Rate:	Slower than Diethyl Ether	Auto-Ignition Temperature, °F	Not Measured
Vapor Density:	Heavier than Air	Vapor Pressure, mmHg:	Not Measured

(See "Other information" Section for abbreviation legend)

10. Stability and Reactivity

STABILITY: Stable under recommended storage conditions.

CONDITIONS TO AVOID: Heat, flames and sparks. Extremes of temperature and direct sunlight.

INCOMPATIBILITY: Keep away from strong oxidizing agents, heat and open flames.

HAZARDOUS DECOMPOSITION PRODUCTS: Incomplete combustion may produce carbon monoxide and other toxic gases.

11. Toxicological Information



Practical Experiences

EFFECT OF OVEREXPOSURE - INHALATION: Inhalation may cause mild irritation to the respiratory tract (nose, mouth, mucous membranes). Inhalation of high concentrations may cause headache, nausea, and dizziness.

EFFECT OF OVEREXPOSURE - SKIN CONTACT: Prolonged and repeated skin contact may cause irritation and possibly dermatitis. Prolonged and repeated skin contact may cause dermatitis, drying and defatting due to the solvent properties.

EFFECT OF OVEREXPOSURE - EYE CONTACT: Mist and vapors may cause eye irritation.

EFFECT OF OVEREXPOSURE - INGESTION: Harmful if swallowed. May cause nausea, vomiting, and diarrhea.

CARCINOGENICITY: This product may contain Titanium Dioxide, which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence of carcinogenicity in humans and sufficient evidence in experimental animals. This classification is relevant when exposed to titanium dioxide in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below

<u>CAS-No.</u> 98-56-6	Chemical Name BENZENE,1-CHLORO-4	<u>Oral LD50</u> Rat - > 6.8 g/kg	<mark>Dermal LD50</mark> Rabbit - > 2.7 g/kg	<u>Vapor LC50</u> N.I.
13463-41-7	(TRIFLUOROMETHYL) 1-HYDROXYPYRIDINE-2-THIONE ZINC SAI T	Rat - 269 mg/kg	Rabbit - >2000 mg/kg	N.I.
1330-20-7	XYLENE MIXTURE OF ISOMERS	Rat - 4300 mg/kg	Rabbit - >1700 mg/kg	N.I.
107-98-2	1-METHOXY-2-PROPANOL	Mouse - 11700 mg/kg	Rabbit - 13000 mg/kg	N.I.
100-41-4	ETHYL BENZENE	Rat - 3500 mg/kg	Rabbit - 15433 mg/kg	N.I.
540-88-5	TERT-BUTYL ACETATE	Rat - male - 4100 mg/ kg	Rabbit - >2000 mg/kg	N.I.
122454-29-9	4-BROMO-2-(4-CHLOROPHENYL)-5- (TRIFLUOROMETHYL)-1H-PYRROLE-3- CARBONITRILE	Rat - 28.7 mg/kg	Guinea pig female - 520-750 mg/kg	N.I.

12. Ecological Information

ECOLOGICAL INFORMATION: No information on ecology is available.

13. Disposal Information



Product

PESTICIDE DISPOSAL: Pesticide wastes are toxic. Open dumping is prohibited. To avoid waste, use all material in this container by application according to label directions. If wastes cannot be avoided, offer remaining product to a waste disposal facility or pesticide disposal program. Waste product should be chemically reprocessed or disposed of according to procedures approved by Federal, State or local authorities.

CONTAINER DISPOSAL: Nonrefillable container. Do not reuse or refill this container. Prior to container disposal, allow any remaining paint residue in the container to air dry. Dispose of the container in accordance with Federal, State or local disposal regulations.

DISPOSAL METHOD: Dispose of material in accordance with applicable federal, state and local regulations.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Dike to prevent entering any sewer or waterway. Transfer liquid to a holding container. Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust. Remove all sources of ignition, ventilate area and remove with inert absorbent and non-sparking tools. Dispose of according to local, state, and federal regulations. Do not incinerate closed containers. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Ventilate area, isolate spilled material, and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

14. Transport Information

SPECIAL TRANSPORT PRECAUTIONS: No special transport precautions are necessary.

	Domestic (USDOT)	International (IMDG)	Air (IATA)
UN Number:	1263	1263	1263
Proper Shipping Name:	Paint	Paint	Paint
Hazard Class:	3	3	3
Packing Group	11	11	II, Cargo Aircraft Only, if >5 L to 60 L Max
Limited Quantity:	No	Yes	No, 1 L per pkg

15. Regulatory Information

U.S. Federal Regulations:

U.S. PESTICIDE LAW

EPA STATEMENT: This chemical is a pesticide product registered by the United States Environmental Protection Agency and is subject to certain labeling requirements under federal pesticide law. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS), and for workplace labels of non-pesticide chemicals. The hazard information required on the pesticide label is reproduced below. The pesticide label also includes other important information, including directions for use.

EPA PESTICIDE LABEL: WARNING. Causes substantial but temporary eye injury. Wear goggles or face shield. Harmful if swallowed. Harmful if inhaled. Do not breathe vapors or spray mist. While spraying paint or sanding or sandblasting boat surfaces, wear a mask or a respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health. Contact your supplier for recommendations on the appropriate respirator and filter. Avoid contact with skin, eyes, or clothing. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco, or using the toilet. Remove and wash contaminated clothing before reuse. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants, and hat.

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Flammable (gases, aerosols, liquids, or solids), Carcinogenicity, Acute Toxicity (any route of exposure), Reproductive toxicity, Serious eye damage or eye irritation, Specific target organ toxicity (single or repeated exposure)

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

Chemical Name	CAS-No.
ZINC OXIDE	1314-13-2
1-HYDROXYPYRIDINE-2-THIONE ZINC SALT	13463-41-7
XYLENE MIXTURE OF ISOMERS	1330-20-7
ETHYL BENZENE	100-41-4
TERT-BUTANOL	75-65-0
METHANOL	67-56-1
2-PENTANONE, 4-METHYL;HEXANONE	108-10-1

TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA components exist in this product.

U.S. State Regulations:

NEW JERSEY RIGHT-TO-KNOW:

The following materials are non-hazardous, but are among the top five components in this product.

Chemical Name	CAS-No.
NON-HAZARDOUS INGREDIENT	TRADE SECRET

PENNSYLVANIA RIGHT-TO-KNOW

The following non-hazardous ingredients are present in the product at greater than 3%.

Chemical Name	CAS-No.
NON-HAZARDOUS INGREDIENT	TRADE SECRET
BARIUM SULFATE	7727-43-7
HYDROUS MAGNESIUM SILICATE	14807-96-6

CALIFORNIA PROPOSITION 65 CARCINOGENS

Warning: The following ingredients present in the product are known to the state of California to cause Cancer.

Chemical Name	CAS-No.
BENZENE,1-CHLORO-4 (TRIFLUOROMETHYL)	98-56-6
ETHYL BENZENE	100-41-4
HYDROUS MAGNESIUM SILICATE	14807-96-6
CRYSTALLINE SILICA, QUARTZ	14808-60-7

CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

Chemical Name METHANOL CAS-No. 67-56-1

International Regulations: As follows -

CANADIAN WHMIS:

This SDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

WHMIS Class B2,D1A,D2A,E

16. Other Information							
Revision Date:	2/23/2023			Supers	edes Date:	New MSDS	
Reason for revision:	on for revision: No Information						
Datasheet produced by: Regulatory Department							
HMIS Ratings:							
Health: 3	Flammability:	2	Reactivity:	0 Pe	ersonal Protection:	J	

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H226	Flammable liquid and vapour.
H300	Fatal if swallowed.
H301	Toxic if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer. Classified as Category 2 based on limited evidence on human and/or animal studies. Mixtures with concentrations of suspected carcinogens ingredients at concentration present
	between 0.1% and 1.0% labelling the SDS will be optional depending on authorities. If Category 2
	carcinogenic present at a concentration of 1% or above labelling the SDS will be expected. Routes of
	exposure are dependant on ingredient form.
H360	May damage fertility or the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs (hematopoietic system [blood forming], blood, bone marrow, immune system) through prolonged or repeated exposure.

Icons for GHS Pictograms shown in Section 3 describing each ingredient:



Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product where instructions and recommendations are not followed.