

1. Identification

| | |
|---------------------------------------|--|
| Product Information: | 3538SP5000 |
| Product Name: | SEAJET 038 TAISHO DARK GREY |
| Recommended Use: | ANTI-FOULING PAINT |
| Supplied by: | CMP Coatings, Inc. 1610 Engineers Rd. Belle Chasse, LA 70037 |
| Emergency Telephone: | Chemtrec 24 Hour Emergency Hotline: 800-424-9300 |
| Safety Data Sheet Coordinator: | SDS@cmpusa.com |

2. Hazards Identification

EMERGENCY OVERVIEW: Extremely Flammable! Eye irritant.

GHS Classification

Acute Tox. 2 Inhalation, Acute Tox. 2 Oral, Carc. 2, Eye Dam. 1, Flam. Liq. 2, Repr. 1A, STOT RE 2

Symbol(s) of Product



Signal Word

Danger

Possible Hazards

56% of the mixture consists of ingredients of unknown acute toxicity

GHS HAZARD STATEMENTS

| | | |
|--|------|---|
| Acute Toxicity, Inhalation, category 2 | H330 | Fatal if inhaled. |
| Acute Toxicity, Oral, category 2 | H300 | Fatal if swallowed. |
| Carcinogenicity, category 2 | H351 | Suspected of causing cancer. Classified as Category 2 based on limited evidence on human and/or animal studies. Mixtures with concentrations of suspected carcinogens ingredients at concentration present between 0.1% and 1.0% labelling the SDS will be optional depending on authorities. If Category 2 carcinogenic present at a concentration of 1% or above labelling the SDS will be expected. Routes of exposure are dependant on ingredient form. |
| Flammable Liquid, category 2 | H225 | Highly flammable liquid and vapour. |
| Reproductive Toxicity, category 1A | H360 | May damage fertility or the unborn child. Classified Category 1A known human reproductive toxicant Category 1B presumed human reproductive toxicant. Irreversible effects such as structural malfunctions, embryo/foetal lethality, post natal functional deficiencies. |
| STOT, repeated exposure, category 2 | H373 | May cause damage to organs (hematopoietic system [blood forming], blood, bone marrow, immune system) through prolonged or repeated exposure. |
| Serious Eye Damage, category 1 | H318 | Causes serious eye damage. |

GHS LABEL PRECAUTIONARY STATEMENTS

| | |
|------|--|
| P201 | Obtain special instructions before use. |
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P260 | Do not breathe dust/fume/gas/mist/vapours/spray. |

| | |
|----------------|--|
| P264 | Wash ... thoroughly after handling. |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection. |
| P281 | Use personal protective equipment as required. |
| P284 | [In case of inadequate ventilation] wear respiratory protection. |
| P301+P310 | IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. |
| P304+P340 | IF INHALED: Remove person to fresh air and keep comfortable for breathing. |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P308+P313 | IF exposed or concerned: Get medical advice/attention. |
| P330 | Rinse mouth. |
| P403+P233 | Store in a well-ventilated place. Keep container tightly closed. |

GHS SDS PRECAUTIONARY STATEMENTS

| | |
|------|---|
| P240 | Ground/bond container and receiving equipment. |
| P241 | Use explosion-proof electrical/ventilating/lighting/.../ equipment. |
| P242 | Use only non-sparking tools. |
| P243 | Take precautionary measures against static discharge. |
| P270 | Do no eat, drink or smoke when using this product. |

3. Composition/Information on Ingredients

| <u>Chemical Name</u> | <u>CAS-No.</u> | <u>Wt. %</u> | <u>GHS Symbols</u> | <u>GHS Statements</u> |
|--|----------------|--------------|--------------------|-----------------------|
| ZINC OXIDE | 1314-13-2 | 10-25 | No Information | No Information |
| 1-HYDROXYPYRIDINE-2-THIONE ZINC SALT | 13463-41-7 | 10-25 | GHS05-GHS06 | H301-318-331 |
| BENZENE,1-CHLORO-4 (TRIFLUOROMETHYL) | 98-56-6 | 2.5-10 | GHS07-GHS08 | H336-373 |
| XYLENE MIXTURE OF ISOMERS | 1330-20-7 | 2.5-10 | GHS02-GHS07 | H226-312-315-332 |
| 1-METHOXY-2-PROPANOL | 107-98-2 | 2.5-10 | GHS02-GHS07-GHS08 | H226-336-360 |
| ETHYL BENZENE | 100-41-4 | 2.5-10 | GHS07-GHS08 | H304-332-351-373 |
| TERT-BUTYL ACETATE | 540-88-5 | 2.5-10 | No Information | No Information |
| TITANIUM DIOXIDE | 13463-67-7 | 2.5-10 | No Information | No Information |
| 4-BROMO-2-(4-CHLOROPHENYL)-5-(TRIFLUOROMETHYL)-1H-PYRROLE-3-CARBONITRILE | 122454-29-9 | 2.5-10 | GHS06-GHS08 | H300-311-330-372 |

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

4. First-aid Measures

FIRST AID - INHALATION: If inhaled, remove to fresh air. Administer oxygen if necessary. Consult a physician if symptoms persist or exposure was severe.

FIRST AID - SKIN CONTACT: In case of contact, wash skin immediately with soap and water. Launder clothing before reuse. Destroy contaminated leather articles.

FIRST AID - EYE CONTACT: If material gets into eyes, flush with water immediately for 15 minutes. Consult a physician.

FIRST AID - INGESTION: If ingested, DO NOT induce vomiting. If conscious, drink 8-10 oz. of water promptly. Call a physician immediately.

5. Fire-fighting Measures

UNUSUAL FIRE AND EXPLOSION HAZARDS: Flammable liquid. Vapors can form an ignitable mixture with air. Vapors can flow along surfaces to a distant ignition source and flash back.

SPECIAL FIREFIGHTING PROCEDURES: Use a self-contained breathing apparatus with full facepiece operated in pressure-demand or other positive pressure mode. Flammable. Cool fire-exposed containers using water spray.

EXTINGUISHING MEDIA: Alcohol Foam, Carbon Dioxide, Dry Chemical, Foam, Water Fog

6. Accidental Release Measures

ENVIRONMENTAL PRECAUTIONS: Contain any spills immediately and dike area to prevent spreading. Package material and

dispose of as hazardous waste.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Dike to prevent entering any sewer or waterway. Transfer liquid to a holding container. Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust. Remove all sources of ignition, ventilate area and remove with inert absorbent and non-sparking tools. Dispose of according to local, state, and federal regulations. Do not incinerate closed containers. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Ventilate area, isolate spilled material, and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

7. Handling and Storage



HANDLING: Flammable liquid. Avoid heat, sparks and open flames. Avoid breathing vapor and contact with eyes, skin and clothing. Hazardous residue may remain in emptied container. Do not reuse empty containers without commercial cleaning or reconditioning. Material will accumulate static charges which may cause an electrical spark (ignition source). Use proper grounding procedures.

STORAGE: Keep container closed when not in use.

8. Exposure Controls/Personal Protection

Ingredients with Occupational Exposure Limits

| <u>Chemical Name</u> | <u>ACGIH TLV-TWA</u> | <u>ACGIH-TLV STEL</u> | <u>OSHA PEL-TWA</u> | <u>OSHA PEL-CEILING</u> |
|--|----------------------|-----------------------|--|-------------------------|
| ZINC OXIDE | N.E. | N.E. | 5 mg/m ³ (dust; respirable) | N.E. |
| 1-HYDROXYPYRIDINE-2-THIONE ZINC SALT | N.E. | N.E. | N.E. | N.E. |
| BENZENE, 1-CHLORO-4 (TRIFLUOROMETHYL) | N.E. | N.E. | N.E. | N.E. |
| XYLENE MIXTURE OF ISOMERS | 100 ppm | 150 ppm | 100 ppm | N.E. |
| 1-METHOXY-2-PROPANOL | 50 ppm | 100 ppm | N.E. | N.E. |
| ETHYL BENZENE | 20 ppm | 125 ppm | 100 ppm | N.E. |
| TERT-BUTYL ACETATE | 200 ppm | N.E. | 200 ppm | N.E. |
| TITANIUM DIOXIDE | 10 mg/m ³ | N.E. | 15 mg/m ³ | N.E. |
| 4-BROMO-2-(4-CHLOROPHENYL)-5-(TRIFLUOROMETHYL)-1H-PYRROLE-3-CARBONITRILE | N.E. | N.E. | 0.040 mg/m ³ | N.E. |

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation
Sk = Skin Sensitizer N.E. = Not Established

Personal Protection



RESPIRATORY PROTECTION: Respirator use is not expected to be necessary under normal conditions of handling. In emergency situations, use of a NIOSH-approved respirator may be required. When concentrations exceed the exposure limits specified, use of a NIOSH-approved dust, mist and fume respirator is recommended. Where the protection factor of the respirator may be exceeded, use of a full facepiece, supplied air, or Self Contained Breathing Apparatus (SCBA) may be necessary.



SKIN PROTECTION: Chemical-resistant gloves may be required for individuals with sensitive skin.



EYE PROTECTION: Ensure that eyewash stations and safety showers are close to the workstation location. Chemical resistant goggles must be worn.



OTHER PROTECTIVE EQUIPMENT: Use personal protective equipment as necessary. Safety shower and eyewash station should be located in immediate work area.



HYGIENIC PRACTICES: Contaminated clothing should be changed and washed before reuse. Eating, drinking and smoking in immediate work area should be prohibited. Keep away from food, drink and animal feeding stuffs.

9. Physical and Chemical Properties

| | | | |
|--------------------------------------|---------------------------|--|-----------------|
| Appearance: | Paint | Physical State: | Liquid |
| Odor: | Solvent | Odor Threshold: | Not Established |
| Density, g/cm³: | 1.563 | pH: | Not Applicable |
| Freeze Point, °F: | No Information | Viscosity: | No Information |
| Solubility in Water: | Insoluble | Partition Coefficient, n-octanol/water: | Not Measured |
| Decomposition temperature, °F | Not Measured | | |
| Boiling Range, °F: | 149 - 284 | Explosive Limits, %: | 0.9 - 10.5 |
| Combustibility: | Supports Combustion | Flash Point, °F: | 67 |
| Evaporation Rate: | Slower than Diethyl Ether | Auto-Ignition Temperature, °F | Not Measured |
| Vapor Density: | Heavier than Air | Vapor Pressure, mmHg: | Not Measured |

(See "Other information" Section for abbreviation legend)

10. Stability and Reactivity

STABILITY: Stable under recommended storage conditions.

CONDITIONS TO AVOID: Heat, flames and sparks. Extremes of temperature and direct sunlight.

INCOMPATIBILITY: Keep away from strong oxidizing agents, heat and open flames.

HAZARDOUS DECOMPOSITION PRODUCTS: Incomplete combustion may produce carbon monoxide and other toxic gases.

11. Toxicological Information



Practical Experiences

EFFECT OF OVEREXPOSURE - INHALATION: Inhalation may cause mild irritation to the respiratory tract (nose, mouth, mucous membranes). Inhalation of high concentrations may cause headache, nausea, and dizziness.

EFFECT OF OVEREXPOSURE - SKIN CONTACT: Prolonged and repeated skin contact may cause irritation and possibly dermatitis. Prolonged and repeated skin contact may cause dermatitis, drying and defatting due to the solvent properties.

EFFECT OF OVEREXPOSURE - EYE CONTACT: Mist and vapors may cause eye irritation.

EFFECT OF OVEREXPOSURE - INGESTION: Harmful if swallowed. May cause nausea, vomiting, and diarrhea.

CARCINOGENICITY: This product may contain Titanium Dioxide, which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence of carcinogenicity in humans and sufficient evidence in experimental animals. This classification is relevant when exposed to titanium dioxide in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below

| <u>CAS-No.</u> | <u>Chemical Name</u> | <u>Oral LD50</u> | <u>Dermal LD50</u> | <u>Vapor LC50</u> |
|----------------|---------------------------------------|---------------------|----------------------|-------------------|
| 13463-41-7 | 1-HYDROXYPYRIDINE-2-THIONE ZINC SALT | Rat - 269 mg/kg | Rabbit - >2000 mg/kg | N.I. |
| 98-56-6 | BENZENE, 1-CHLORO-4 (TRIFLUOROMETHYL) | Rat - > 6.8 g/kg | Rabbit - > 2.7 g/kg | N.I. |
| 1330-20-7 | XYLENE MIXTURE OF ISOMERS | Rat - 4300 mg/kg | Rabbit - >1700 mg/kg | N.I. |
| 107-98-2 | 1-METHOXY-2-PROPANOL | Mouse - 11700 mg/kg | Rabbit - 13000 mg/kg | N.I. |
| 100-41-4 | ETHYL BENZENE | Rat - 3500 mg/kg | Rabbit - 15433 mg/kg | N.I. |

| | | | | |
|-------------|--|-----------------------------|--------------------------------------|------|
| 540-88-5 | TERT-BUTYL ACETATE | Rat - male - 4100 mg/ kg | Rabbit - >2000 mg/kg | N.I. |
| 13463-67-7 | TITANIUM DIOXIDE | >10000 mg/kg | >10000 mg/kg | N.I. |
| 122454-29-9 | 4-BROMO-2-(4-CHLOROPHENYL)-5-(TRIFLUOROMETHYL)-1H-PYRROLE-3-CARBONITRILE | Rat - 28.7 mg/kg | Guinea pig female - 520-750 mg/kg | N.I. |

N.I. = No Information

12. Ecological Information

ECOLOGICAL INFORMATION: No information on ecology is available.

13. Disposal Information



Product

PESTICIDE DISPOSAL: Pesticide wastes are toxic. Open dumping is prohibited. To avoid waste, use all material in this container by application according to label directions. If wastes cannot be avoided, offer remaining product to a waste disposal facility or pesticide disposal program. Waste product should be chemically reprocessed or disposed of according to procedures approved by Federal, State or local authorities.

CONTAINER DISPOSAL: Nonrefillable container. Do not reuse or refill this container. Prior to container disposal, allow any remaining paint residue in the container to air dry. Dispose of the container in accordance with Federal, State or local disposal regulations.

DISPOSAL METHOD: Dispose of material in accordance with applicable federal, state and local regulations.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Dike to prevent entering any sewer or waterway. Transfer liquid to a holding container. Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust. Remove all sources of ignition, ventilate area and remove with inert absorbent and non-sparking tools. Dispose of according to local, state, and federal regulations. Do not incinerate closed containers. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Ventilate area, isolate spilled material, and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

14. Transport Information

SPECIAL TRANSPORT PRECAUTIONS: No special transport precautions are necessary.

| | Domestic (USDOT) | International (IMDG) | Air (IATA) |
|-----------------------|------------------|----------------------|--|
| UN Number: | 1263 | 1263 | 1263 |
| Proper Shipping Name: | Paint | Paint | Paint |
| Hazard Class: | 3 | 3 | 3 |
| Packing Group | II | II | II, Cargo Aircraft Only, if >5 L to 60 L Max |
| Limited Quantity: | No | Yes | No, 1 L per pkg |

15. Regulatory Information

U.S. Federal Regulations:

U.S. PESTICIDE LAW

EPA STATEMENT: This chemical is a pesticide product registered by the United States Environmental Protection Agency and is subject to certain labeling requirements under federal pesticide law. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS), and for workplace labels of non-pesticide chemicals. The hazard information required on the pesticide label is reproduced below. The pesticide label also includes other important information, including directions for use.

EPA PESTICIDE LABEL: WARNING. Causes substantial but temporary eye injury. Wear goggles or face shield. Harmful if swallowed. Harmful if inhaled. Do not breathe vapors or spray mist. While spraying paint or sanding or sandblasting boat surfaces, wear a mask or a respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health. Contact your supplier for recommendations on the appropriate respirator and filter. Avoid contact with skin, eyes, or clothing. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco, or using the toilet. Remove and wash contaminated clothing before reuse. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants, and hat.

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Flammable (gases, aerosols, liquids, or solids), Carcinogenicity, Acute Toxicity (any route of exposure), Reproductive toxicity, Serious eye damage or eye irritation, Specific target organ toxicity (single or repeated exposure)

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

| <u>Chemical Name</u> | <u>CAS-No.</u> |
|--------------------------------------|----------------|
| ZINC OXIDE | 1314-13-2 |
| 1-HYDROXYPYRIDINE-2-THIONE ZINC SALT | 13463-41-7 |
| XYLENE MIXTURE OF ISOMERS | 1330-20-7 |
| ETHYL BENZENE | 100-41-4 |
| TERT-BUTANOL | 75-65-0 |
| METHANOL | 67-56-1 |
| 2-PENTANONE, 4-METHYL;HEXANONE | 108-10-1 |

TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA components exist in this product.

U.S. State Regulations:

NEW JERSEY RIGHT-TO-KNOW:

The following materials are non-hazardous, but are among the top five components in this product.

| <u>Chemical Name</u> | <u>CAS-No.</u> |
|--------------------------|----------------|
| NON-HAZARDOUS INGREDIENT | TRADE SECRET |

PENNSYLVANIA RIGHT-TO-KNOW

The following non-hazardous ingredients are present in the product at greater than 3%.

| <u>Chemical Name</u> | <u>CAS-No.</u> |
|----------------------------|----------------|
| NON-HAZARDOUS INGREDIENT | TRADE SECRET |
| HYDROUS MAGNESIUM SILICATE | 14807-96-6 |
| BARIUM SULFATE | 7727-43-7 |

CALIFORNIA PROPOSITION 65 CARCINOGENS

Warning: The following ingredients present in the product are known to the state of California to cause Cancer.

| <u>Chemical Name</u> | <u>CAS-No.</u> |
|--------------------------------------|----------------|
| BENZENE,1-CHLORO-4 (TRIFLUOROMETHYL) | 98-56-6 |
| ETHYL BENZENE | 100-41-4 |
| HYDROUS MAGNESIUM SILICATE | 14807-96-6 |
| TITANIUM DIOXIDE | 13463-67-7 |
| CRYSTALLINE SILICA, QUARTZ | 14808-60-7 |

CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

| <u>Chemical Name</u> | <u>CAS-No.</u> |
|----------------------|----------------|
| METHANOL | 67-56-1 |

International Regulations: As follows -**CANADIAN WHMIS:**

This SDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

WHMIS Class B2,D1A,D2A,E

16. Other Information

| | | | |
|------------------------|-----------------------|------------------|----------|
| Revision Date: | 2/23/2023 | Supersedes Date: | New MSDS |
| Reason for revision: | No Information | | |
| Datasheet produced by: | Regulatory Department | | |

HMIS Ratings:

| | | | | | | | |
|---------|---|---------------|---|-------------|---|----------------------|---|
| Health: | 3 | Flammability: | 2 | Reactivity: | 0 | Personal Protection: | J |
|---------|---|---------------|---|-------------|---|----------------------|---|

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

| | |
|------|---|
| H226 | Flammable liquid and vapour. |
| H300 | Fatal if swallowed. |
| H301 | Toxic if swallowed. |
| H304 | May be fatal if swallowed and enters airways. |
| H311 | Toxic in contact with skin. |
| H312 | Harmful in contact with skin. |
| H315 | Causes skin irritation. |
| H318 | Causes serious eye damage. |
| H330 | Fatal if inhaled. |
| H331 | Toxic if inhaled. |
| H332 | Harmful if inhaled. |
| H336 | May cause drowsiness or dizziness. |
| H351 | Suspected of causing cancer. Classified as Category 2 based on limited evidence on human and/or animal studies. Mixtures with concentrations of suspected carcinogens ingredients at concentration present between 0.1% and 1.0% labelling the SDS will be optional depending on authorities. If Category 2 carcinogenic present at a concentration of 1% or above labelling the SDS will be expected. Routes of exposure are dependant on ingredient form. |
| H360 | May damage fertility or the unborn child. |
| H372 | Causes damage to organs through prolonged or repeated exposure. |
| H373 | May cause damage to organs (hematopoietic system [blood forming], blood, bone marrow, immune system) through prolonged or repeated exposure. |

Icons for GHS Pictograms shown in Section 3 describing each ingredient:

GHS02



GHS05



GHS06



GHS07



GHS08



Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product where instructions and recommendations are not followed.