

Date Printed: 8/1/2024

# Safety Data Sheet

Product: 3540SP1000

1. Identification	
Product Information:	3540SP1000
Product Name:	SEAJET 041 POSEIDON BLACK
Recommended Use:	ANTI-FOULING PAINT
Supplied by:	CMP Coatings, Inc. 1610 Engineers Rd. Belle Chasse, LA 70037
Emergency Telephone: Safety Data Sheet Coordinator:	Chemtrec 24 Hour Emergency Hotline: 800-424-9300 SDS@cmpusa.com

## 2. Hazards Identification

**EMERGENCY OVERVIEW:** FLAMMABLE liquid and vapor. COMBUSTIBLE liquid and vapor. Eye irritant.

#### **GHS Classification**

Acute Tox. 4 Inhalation, Acute Tox. 4 Oral, Carc. 1A, Eye Irrit. 2A, Flam. Liq. 3, Resp. Sens. 1, Skin Irrit. 2, Skin Sens. 1, STOT RE 2

#### Symbol(s) of Product



Signal Word Danger

#### Possible Hazards

61% of the mixture consists of ingredients of unknown acute toxicity

#### GHS HAZARD STATEMENTS

Acute Toxicity, Inhalation, category 4	H332	Harmful if inhaled.	
Acute Toxicity, Oral, category 4	H302	Harmful if swallowed.	
Carcinogenicity, category 1A	H350	May cause cancer. Classified as carcinogenic Category 1 on the basis of epidemiological and/or animal data. Mixtures are classified as carcinogenic when at least 1 ingredient has been classified as carcinogenic and is present at 0.1% or above. Routes of exposure are dependent on ingredient form.May cause cancer.	
Eye Irritation, category 2A	H319	Causes serious eye irritation.	
Flammable Liquid, category 3	H226	Flammable liquid and vapour.	
Respiratory Sensitizer, category 1	H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.	
STOT, repeated exposure, category 2	H373	May cause damage to organs (hematopoietic system [blood forming], blood, bone marrow, immune system) through prolonged or repeated exposure.	
Skin Irritation, category 2	H315	Causes skin irritation.	
Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.	
GHS LABEL PRECAUTIONARY STAT	EMENTS		
P201	Obtain special instructions before use.		
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.		
P260	Do not bre	athe dust/fume/gas/mist/vapours/spray.	
P280	Wear prote	ective gloves/protective clothing/eye protection/face protection.	

P285	In case of inadequate ventilation wear respiratory protection.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P304+P341	IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P342+P311	If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.
P362	Take off contaminated clothing.
GHS SDS PRECAUTIONARY STATEME	ENTS
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting// equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P270	Do no eat, drink or smoke when using this product.
P363	Wash contaminated clothing before reuse.

## 3. Composition/Information on Ingredients

Chemical Name	CAS-No.	Wt. % GHS Symbols	GHS Statements
COPPER(I) OXIDE	1317-39-1	10-25 GHS07	H302
ZINC OXIDE	1314-13-2	10-25 No Information	No Information
XYLENE MIXTURE OF ISOMERS	1330-20-7	10-25 GHS02-GHS07	H226-312-315-332
GUM ROSIN	8050-09-7	2.5-10 GHS07-GHS08	H302-315-317-319-334
FELDSPAR	68476-25-5	2.5-10 GHS08	H372
PROPRIETARY RESIN	TRADE	2.5-10 No Information	No Information
	SECRET		
ETHANOL, 2-BUTOXY-, 1,1',1"-PHOSPHATE	78-51-3	2.5-10 GHS07	H312-315-319-332-335
ETHYL BENZENE	100-41-4	1.0-2.5 GHS07-GHS08	H304-332-351-373
2-PENTANONE, 4-METHYL;HEXANONE	108-10-1	1.0-2.5 GHS07	H319-332-336
4,5-DICHLORO-2-N-OCTYL-4-ISOTHIAZOLIN-3-	64359-81-5	1.0-2.5 GHS07	H315-317-319
ONE			
CRYSTALLINE SILICA, QUARTZ	14808-60-7	0.1-1.0 GHS08	H350-372
POLYAMINE AMIDE SALT	TRADE	0.1-1.0 No Information	No Information
	SECRET		
METHYL BENZENE	108-88-3	0.1-1.0 GHS07-GHS08	H304-315-319-336-361-373

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

## 4. First-aid Measures



**FIRST AID - INHALATION:** If inhaled, remove to fresh air. Administer oxygen if necessary. Consult a physician if symptoms persist or exposure was severe.

**FIRST AID - SKIN CONTACT:** In case of contact, wash skin immediately with soap and water. Launder clothing before reuse. Destroy contaminated leather articles.

FIRST AID - EYE CONTACT: If material gets into eyes, flush with water immediately for 15 minutes. Consult a physician.

**FIRST AID - INGESTION:** If ingested, DO NOT induce vomiting. If conscious, drink 8-10 oz. of water promptly. Call a physician immediately.

## 5. Fire-fighting Measures

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Flammable liquid. Vapors can form an ignitable mixture with air. Vapors can flow along surfaces to a distant ignition source and flash back.

**SPECIAL FIREFIGHTING PROCEDURES:** Use a self-contained breathing apparatus with full facepiece operated in pressure demand or other positive pressure mode. Flammable. Cool fire-exposed containers using water spray.

#### EXTINGUISHING MEDIA: Alcohol Foam, Carbon Dioxide, Dry Chemical, Foam, Water Fog

#### 6. Accidental Release Measures

**ENVIRONMENTAL PRECAUTIONS:** Contain any spills immediately and dike area to prevent spreading. Package material and dispose of as hazardous waste.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Dike to prevent entering any sewer or waterway. Transfer liquid to a holding container. Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust. Remove all sources of ignition, ventilate area and remove with inert absorbent and non-sparking tools. Dispose of according to local, state, and federal regulations. Do not incinerate closed containers. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Ventilate area, isolate spilled material, and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

## 7. Handling and Storage



**HANDLING:** Flammable liquid. Avoid heat, sparks and open flames. Avoid breathing vapor and contact with eyes, skin and clothing. Hazardous residue may remain in emptied container. Do not reuse empty containers without commercial cleaning or reconditioning. Material will accumulate static charges which may cause an electrical spark (ignition source). Use proper grounding procedures.

STORAGE: Keep container closed when not in use.

#### 8. Exposure Controls/Personal Protection

Ingredients with Occupational Exposu Chemical Name	ire Limits ACGIH TLV-TWA	ACGIH-TLV STEL	OSHA PEL-TWA	OSHA PEL-CEILING
COPPER(I) OXIDE	N.E.	N.E.	N.E.	N.E.
ZINC OXIDE	N.E.	N.E.	5 mg/m3 (dust; respirable)	N.E.
XYLENE MIXTURE OF ISOMERS	100 ppm	150 ppm	100 ppm	N.E.
GUM ROSIN	N.E.	N.E.	N.E.	N.E.
FELDSPAR	N.E.	N.E.	N.E.	N.E.
PROPRIETARY RESIN	N.E.	N.E.	N.E.	N.E.
ETHANOL, 2-BUTOXY-, 1,1',1"-	N.E.	N.E.	N.E.	N.E.
PHOSPHATE				
ETHYL BENZENE	20 ppm	125 ppm	100 ppm	N.E.
2-PENTANONE, 4-METHYL;HEXANONE	E 20 ppm	75 ppm	50 ppm	N.E.
4,5-DICHLORO-2-N-OCTYL-4-	N.E.	N.E.	N.E.	N.E.
ISOTHIAZOLIN-3-ONE				
CRYSTALLINE SILICA, QUARTZ	8 hr - 0.025 mg/m3	N.E.	8 hr - 10 mg/m3 / Silica + 2	% N.E.
POLYAMINE AMIDE SALT	N.E.	N.E.	N.E.	N.E.
METHYL BENZENE	20 ppm	N.E.	200 ppm	300 ppm

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation Sk = Skin Sensitizer N.E. = Not Established

#### Personal Protection



**RESPIRATORY PROTECTION:** Respirator use is not expected to be necessary under normal conditions of handling. In emergency situations, use of a NIOSH-approved respirator may be required. When concentrations exceed the exposure limits specified, use of a NIOSH-approved dust, mist and fume respirator is recommended. Where the protection factor of the respirator may be exceeded, use of a full facepiece, supplied air, or Self Contained Breathing Apparatus (SCBA) may be necessary.



SKIN PROTECTION: Chemical-resistant gloves may be required for individuals with sensitive skin.



**EYE PROTECTION:** Ensure that eyewash stations and safety showers are close to the workstation location. Chemical resistant goggles must be worn.



**OTHER PROTECTIVE EQUIPMENT:** Use personal protective equipment as necessary. Safety shower and eyewash station should be located in immediate work area.

**HYGIENIC PRACTICES:** Contaminated clothing should be changed and washed before reuse. Eating, drinking and smoking in immediate work area should be prohibited. Keep away from food, drink and animal feeding stuffs.

## 9. Physical and Chemical Properties

Appearance:	Paint	Physical State:	Liquid
Odor:	Solvent	Odor Threshold:	Not Established
Density, g/cm3:	1.928	pH:	Not Applicable
Freeze Point, °F:	No Information	Viscosity:	No Information
Solubility in Water:	Insoluble	Partition Coefficient, n-octanol/	Not Measured
Decomposition temperature, °F	Not Measured	water:	
Boiling Range, °F:	223 - 442	Explosive Limits, %:	
Combustibility:	Supports Combustion	Flash Point, °F:	91
Evaporation Rate:	Slower than Diethyl Ether	Auto-Ignition Temperature, °F	Not Measured
Vapor Density:	Heavier than Air	Vapor Pressure, mmHg:	Not Measured

(See "Other information" Section for abbreviation legend)

## 10. Stability and Reactivity

STABILITY: Stable under recommended storage conditions.

CONDITIONS TO AVOID: Heat, flames and sparks. Extremes of temperature and direct sunlight.

INCOMPATIBILITY: Keep away from strong oxidizing agents, heat and open flames.

HAZARDOUS DECOMPOSITION PRODUCTS: Incomplete combustion may produce carbon monoxide and other toxic gases.

#### 11. Toxicological Information



**Practical Experiences** 

**EFFECT OF OVEREXPOSURE - INHALATION:** Inhalation may cause mild irritation to the respiratory tract (nose, mouth, mucous membranes). Inhalation of high concentrations may cause headache, nausea, and dizziness.

**EFFECT OF OVEREXPOSURE - SKIN CONTACT:** Prolonged and repeated skin contact may cause irritation and possibly dermatitis. Prolonged and repeated skin contact may cause dermatitis, drying and defatting due to the solvent properties.

EFFECT OF OVEREXPOSURE - EYE CONTACT: Mist and vapors may cause eye irritation.

EFFECT OF OVEREXPOSURE - INGESTION: Harmful if swallowed. May cause nausea, vomiting, and diarrhea.

**CARCINOGENICITY:** This product contains a chemical suspected of causing cancer by the International Agency for Research on Cancer (IARC). Classified as Category 2 based on limited evidence on human and/or animal studies. This product contains a chemical that the International Agency for Research on Cancer (IARC) has concluded is carcinogenic to humans (Group 1).

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

## Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below

CAS-No.	<u>Chemical Name</u>	Oral LD50	Dermal LD50	Vapor LC50
1317-39-1	COPPER(I) OXIDE	Rat - 470 mg/kg	Rat - > 2000 mg/kg	Rat - 4 hr - >50000 mg/m3
1330-20-7	XYLENE MIXTURE OF ISOMERS	Rat - 4300 mg/kg	Rabbit - >1700 mg/kg	N.I.
8050-09-7	GUM ROSIN	Rat - 2800 mg/kg	Rat - >2000 mg/kg	N.I.
100-41-4	ETHYL BENZENE	Rat - 3500 mg/kg	Rabbit - 15433 mg/kg	N.I.
108-10-1	2-PENTANONE, 4-METHYL;HEXANONE	Rat - 2080 mg/kg	Rat - >2000 mg/kg	Rat - 4 hr - 8.2 - 16.4 mg/l
14808-60-7	CRYSTALLINE SILICA, QUARTZ	Rat - >22500 mg/kg	N.I.	N.I.
108-88-3	METHYL BENZENE	Rat - >5580 mg/kg	Rabbit - 12196 mg/kg	Rat - 4 hr - 12500 - 28800 mg/m3

N.I. = No Information

## 12. Ecological Information

ECOLOGICAL INFORMATION: No information on ecology is available.

#### 13. Disposal Information

Product



**PESTICIDE DISPOSAL:** Pesticide wastes are toxic. Open dumping is prohibited. To avoid waste, use all material in this container by application according to label directions. If wastes cannot be avoided, offer remaining product to a waste disposal facility or pesticide disposal program. Waste product should be chemically reprocessed or disposed of according to procedures approved by Federal, State or local authorities.

**CONTAINER DISPOSAL:** Nonrefillable container. Do not reuse or refill this container. Prior to container disposal, allow any remaining paint residue in the container to air dry. Dispose of the container in accordance with Federal, State or local disposal regulations.

**DISPOSAL METHOD:** Dispose of material in accordance with applicable federal, state and local regulations.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Dike to prevent entering any sewer or waterway. Transfer liquid to a holding container. Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust. Remove all sources of ignition, ventilate area and remove with inert absorbent and non-sparking tools. Dispose of according to local, state, and federal regulations. Do not incinerate closed containers. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Ventilate area, isolate spilled material, and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

## 14. Transport Information

SPECIAL TRANSPORT PRECAUTIONS: No special transport precautions are necessary.

[			
	Domestic (USDOT)	International (IMDG)	Air (IATA)
UN Number:	1263	1263	1263
Proper Shipping Name:	Paint	Paint	Paint
Hazard Class:	3	3	3
Packing Group	111	III	111
Limited Quantity:	No	Yes	Yes, 10 L per pkg

## 15. Regulatory Information

## U.S. Federal Regulations:

#### U.S. PESTICIDE LAW

**EPA STATEMENT:** This chemical is a pesticide product registered by the United States Environmental Protection Agency and is subject to certain labeling requirements under federal pesticide law. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS), and for workplace labels of non-pesticide chemicals. The hazard information required on the pesticide label is reproduced below. The pesticide label also includes other important information, including directions for use.

**EPA PESTICIDE LABEL:** CAUTION. Causes moderate eye irritation. Avoid contact with eyes or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants, and hat. While spraying paint or sanding or sandblasting boat surfaces, wear a mask or a respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco or using the toilet.

#### CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Flammable (gases, aerosols, liquids, or solids), Carcinogenicity, Acute Toxicity (any route of exposure), Skin Corrosion or Irritation, Respiratory or Skin Sensitization, Serious eye damage or eye irritation, Specific target organ toxicity (single or repeated exposure)

#### SARA SECTION 313:

. . . .

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

<u>Chemical Name</u>	<u>CAS-No.</u>
COPPER(I) OXIDE	1317-39-1
ZINC OXIDE	1314-13-2
XYLENE MIXTURE OF ISOMERS	1330-20-7
ETHYL BENZENE	100-41-4
2-PENTANONE, 4-METHYL;HEXANONE	108-10-1
COPPER(II) OXIDE	1317-38-0
METHYL BENZENE	108-88-3
CUMENE	98-82-8

#### TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA components exist in this product.

## U.S. State Regulations:

## NEW JERSEY RIGHT-TO-KNOW:

The following materials are non-hazardous, but are among the top five components in this product.

<u>Chemical Name</u>	<u>CAS-No.</u>
HYDROUS MAGNESIUM SILICATE	14807-96-6

#### PENNSYLVANIA RIGHT-TO-KNOW

The following non-hazardous ingredients are present in the product at greater than 3%.

#### **Chemical Name**

HYDROUS MAGNESIUM SILICATE CALCIUM SULFATE HEMI-HYDRATE

CAS-No.	
14807-96-	6
10034-76-	1

#### **CALIFORNIA PROPOSITION 65 CARCINOGENS**

Warning: The following ingredients present in the product are known to the state of California to cause Cancer.

Chemical Name	<u>CAS-No.</u>
HYDROUS MAGNESIUM SILICATE	14807-96-6
ETHYL BENZENE	100-41-4
CRYSTALLINE SILICA, QUARTZ	14808-60-7
CUMENE	98-82-8

#### CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

Chemical Name

METHYL BENZENE

CAS-No. 108-88-3

## International Regulations: As follows -

#### CANADIAN WHMIS:

This SDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

WHMIS Class B2,D2A

## 16. Other Information

Revision D	ate:	8/1/2024	8/1/2024			persedes Date:	8/1/2024
Reason for revision: Datasheet produced by:			Revision Statement(s) Changed Regulatory Department				
HMIS Ratings:							
Health:	3	Flammability:	2	Reactivity:	0	Personal Protection:	J

#### Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eve irritation.
	Harmful if inhaled.
H332	
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H350	May cause cancer.
H351	Suspected of causing cancer. Classified as Category 2 based on limited evidence on human and/or animal studies. Mixtures with concentrations of suspected carcinogens ingredients at concentration present between 0.1% and 1.0% labelling the SDS will be optional depending on authorities. If Category 2 carcinogenic present at a concentration of 1% or above labelling the SDS will be expected. Routes of exposure are dependent on ingredient form.
H361	Suspected of damaging fertility or the unborn child. Classifed Category 2 suspected human reproductive toxicant irreversible effects such as structural malfunctions, embryo/foetal lethality, post natal functional deficiencies.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs (hematopoietic system [blood forming], blood, bone marrow, immune system) through prolonged or repeated exposure.

Icons for GHS Pictograms shown in Section 3 describing each ingredient:

GHS02





Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product where instructions and recommendations are not followed.