

Date Printed: 2/23/2023

# Safety Data Sheet

Product: 3230SP0901A

1. Identification	
Product Information:	3230SP0901A
Product Name:	SEAJET 117 MULTIPURPOSE EPOXY PRIMER, BASE
Recommended Use:	HIGH BUILD EPOXY
Supplied by:	CMP Coatings, Inc. 1610 Engineers Rd. Belle Chasse, LA 70037
Emergency Telephone: Safety Data Sheet Coordinator:	Chemtrec 24 Hour Emergency Hotline: 800-424-9300 SDS@cmpusa.com

# 2. Hazards Identification

EMERGENCY OVERVIEW: Extremely Flammable!Eye irritant.

## **GHS Classification**

Acute Tox. 4 Inhalation, Carc. 1A, Flam. Liq. 2, Muta. 1A, Repr. 1A, Skin Irrit. 2, Skin Sens. 1

## Symbol(s) of Product



Signal Word Danger

# Possible Hazards

64% of the mixture consists of ingredients of unknown acute toxicity

## GHS HAZARD STATEMENTS

GIS HAZARD STATEMENTS			
Acute Toxicity, Inhalation, category 4	H332	Harmful if inhaled.	
Carcinogenicity, category 1A	H350	May cause cancer. Classified as carcinogenic Category 1 on the basis of epidemiological and/or animal data. Mixtures are classified as carcinogenic when at least 1 ingredient has been classified as carcinogenic and is present at 0.1% or above Routes of exposure are dependent on ingredient form.May cause cancer.	
Flammable Liquid, category 2	H225	Highly flammable liquid and vapour.	
Germ Cell Mutagenicity, category 1A	H340	May cause genetic defects . Classified as mutagenic Category 1 if one ingredient is present at or above 0.1% Applies to liquids, Solids (w/w units) and gases (v/v). The substance may also have its own exposure limit. Routes of exposure are dependent on ingredient form.	
Reproductive Toxicity, category 1A	H360	May damage fertility or the unborn child. Classified Category 1A known human reproductive toxicant Category 1B presumed human reproductive toxicant. Irreversible effects such as structural malfunctions, embryo/foetal lethality, post natal functional deficiencies.	
Skin Irritation, category 2	H315	Causes skin irritation.	
Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.	
GHS LABEL PRECAUTIONARY STATE	MENTS		
P201	Obtain special instructions before use.		
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.		
P233	Keep conta	iner tightly closed.	

P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P281	Use personal protective equipment as required.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P362	Take off contaminated clothing.
GHS SDS PRECAUTIONARY STATEME	ENTS
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting// equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P363	Wash contaminated clothing before reuse.

# 3. Composition/Information on Ingredients

Chemical Name	CAS-No.	Wt. % GHS Symbols	GHS Statements
POLY(BISPHENOL A-CO-EPICHLOROHYDRIN), GLYCIDYL END-CAPPED	25036-25-3	10-25 GHS07	H317
XYLENE MIXTURE OF ISOMERS	1330-20-7	10-25 GHS02-GHS07	H226-312-315-332
ALUMINUM	7429-90-5	10-25 No Information	No Information
DIMETHYL CARBONATE	616-38-6	2.5-10 No Information	No Information
TITANIUM DIOXIDE	13463-67-7	2.5-10 No Information	No Information
1-METHOXY-2-PROPANOL	107-98-2	2.5-10 GHS02-GHS07-	H226-336-360
		GHS08	
STODDARD SOLVENT	8052-41-3	2.5-10 GHS08	H304
BISPHENOL A (EPICHLOROHYDRIN) EPOXY RESIN	25068-38-6	2.5-10 GHS07	H315-317-319-335
AROMATIC HYDROCARBON	64742-95-6	2.5-10 GHS07-GHS08	H304-315-332-336-340-350-361
ETHYL BENZENE	100-41-4	1.0-2.5 GHS07-GHS08	H304-332-351-373
GLYCIDOXYPROPYL TRIMETHOXYSILANE	2530-83-8	0.1-1.0 GHS05	H318
POLYAMINE AMIDE SALT	TRADE SECRET	0.1-1.0 No Information	No Information
CRYSTALLINE SILICA, QUARTZ	14808-60-7	0.1-1.0 GHS08	H350-372

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

# 4. First-aid Measures



FIRST AID - INHALATION: If inhaled, remove to fresh air. Administer oxygen if necessary. Consult a physician if symptoms persist or exposure was severe.

**FIRST AID - SKIN CONTACT:** In case of contact, wash skin immediately with soap and water. Launder clothing before reuse. Destroy contaminated leather articles.

FIRST AID - EYE CONTACT: If material gets into eyes, flush with water immediately for 15 minutes. Consult a physician.

**FIRST AID - INGESTION:** If ingested, DO NOT induce vomiting. If conscious, drink 8-10 oz. of water promptly. Call a physician immediately.

# 5. Fire-fighting Measures

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Flammable liquid. Vapors can form an ignitable mixture with air. Vapors can flow along surfaces to a distant ignition source and flash back.

**SPECIAL FIREFIGHTING PROCEDURES:** Use a self-contained breathing apparatus with full facepiece operated in pressure demand or other positive pressure mode. Flammable. Cool fire-exposed containers using water spray.

EXTINGUISHING MEDIA: Alcohol Foam, Carbon Dioxide, Dry Chemical, Foam, Water Fog

# 6. Accidental Release Measures

**ENVIRONMENTAL PRECAUTIONS:** Contain any spills immediately and dike area to prevent spreading. Package material and dispose of as hazardous waste.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Dike to prevent entering any sewer or waterway. Transfer liquid to a holding container. Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust. Remove all sources of ignition, ventilate area and remove with inert absorbent and non-sparking tools. Dispose of according to local, state, and federal regulations. Do not incinerate closed containers. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Ventilate area, isolate spilled material, and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

# 7. Handling and Storage



**HANDLING:** Flammable liquid. Avoid heat, sparks and open flames. Avoid breathing vapor and contact with eyes, skin and clothing. Hazardous residue may remain in emptied container. Do not reuse empty containers without commercial cleaning or reconditioning. Material will accumulate static charges which may cause an electrical spark (ignition source). Use proper grounding procedures.

STORAGE: Keep container closed when not in use.

# 8. Exposure Controls/Personal Protection

Ingredients with Occupational Exposure Limits Chemical Name <u>ACGIH TLV-TWA</u> <u>ACGIH-TLV STEL</u> <u>OSHA PEL-TWA</u> OSHA PEL-C					
POLY(BISPHENOL A-CO- EPICHLOROHYDRIN), GLYCIDYL END- CAPPED	N.E.	N.E.	N.E.	N.E.	
XYLENE MIXTURE OF ISOMERS ALUMINUM DIMETHYL CARBONATE TITANIUM DIOXIDE 1-METHOXY-2-PROPANOL STODDARD SOLVENT BISPHENOL A (EPICHLOROHYDRIN) EPOXY RESIN	100 ppm 1 mg/m3 N.E. 10 mg/m3 50 ppm 100 ppm - 8 hrs N.E.	150 ppm N.E. N.E. N.E. 100 ppm N.E. N.E.	100 ppm 15 mg/m3 N.E. 15 mg/m3 N.E. 500 ppm - 8 hrs N.E.	N.E. N.E. N.E. N.E. N.E. N.E. N.E.	
AROMATIC HYDROCARBON ETHYL BENZENE GLYCIDOXYPROPYL TRIMETHOXYSILANE POLYAMINE AMIDE SALT CRYSTALLINE SILICA, QUARTZ	N.E. 20 ppm 5 ppm N.E. 8 hr - 0.025 mg/m3	N.E. 125 ppm 10 ppm N.E. N.E.	N.E. 100 ppm N.E. N.E. 8 hr - 10 mg/m3 / <sup>6</sup> Silica + 2	N.E. N.E. N.E. N.E. % N.E.	

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation Sk = Skin Sensitizer N.E. = Not Established

#### Personal Protection

**RESPIRATORY PROTECTION:** Respirator use is not expected to be necessary under normal conditions of handling. In emergency situations, use of a NIOSH-approved respirator may be required. When concentrations exceed the exposure limits specified, use of a NIOSH-approved dust, mist and fume respirator is recommended. Where the protection factor of the respirator may be exceeded, use of a full facepiece, supplied air, or Self Contained Breathing Apparatus (SCBA) may be necessary.



SKIN PROTECTION: Chemical-resistant gloves may be required for individuals with sensitive skin.



**EYE PROTECTION:** Ensure that eyewash stations and safety showers are close to the workstation location. Chemical resistant goggles must be worn.



**OTHER PROTECTIVE EQUIPMENT:** Use personal protective equipment as necessary. Safety shower and eyewash station should be located in immediate work area.

**HYGIENIC PRACTICES:** Contaminated clothing should be changed and washed before reuse. Eating, drinking and smoking in immediate work area should be prohibited. Keep away from food, drink and animal feeding stuffs.

# 9. Physical and Chemical Properties

Appearance: Odor: Density, g/cm3: Freeze Point, °F: Solubility in Water: Decomposition temperature, °F	PAINT SOLVENT 1.313 No Information Insoluble Not Measured	Physical State: Odor Threshold: pH: Viscosity: Partition Coefficient, n-octanol/ water:	Liquid Not Established Not Applicable No Information Not Measured
Boiling Range, °F:	149 - 500	Explosive Limits, %:	1.0 - 13.7
Combustibility:	Supports Combustion	Flash Point, °F:	72
Evaporation Rate:	Slower than Diethyl Ether	Auto-Ignition Temperature, °F	Not Measured
Vapor Density:	Heavier than Air	Vapor Pressure, mmHg:	Not Measured

(See "Other information" Section for abbreviation legend)

# 10. Stability and Reactivity

STABILITY: Stable under recommended storage conditions.

CONDITIONS TO AVOID: Heat, flames and sparks. Extremes of temperature and direct sunlight.

**INCOMPATIBILITY:** Keep away from strong oxidizing agents, heat and open flames.

HAZARDOUS DECOMPOSITION PRODUCTS: Incomplete combustion may produce carbon monoxide and other toxic gases.

# 11. Toxicological Information



**Practical Experiences** 

**EFFECT OF OVEREXPOSURE - INHALATION:** Inhalation may cause mild irritation to the respiratory tract (nose, mouth, mucous membranes). Inhalation of high concentrations may cause headache, nausea, and dizziness.

**EFFECT OF OVEREXPOSURE - SKIN CONTACT:** Prolonged and repeated skin contact may cause irritation and possibly dermatitis. Prolonged and repeated skin contact may cause dermatitis, drying and defatting due to the solvent properties.

EFFECT OF OVEREXPOSURE - EYE CONTACT: Mist and vapors may cause eye irritation.

EFFECT OF OVEREXPOSURE - INGESTION: Harmful if swallowed. May cause nausea, vomiting, and diarrhea.

**CARCINOGENICITY:** This product may contain Titanium Dioxide, which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence of carcinogenicity in humans and sufficient evidence in experimental animals. This classification is relevant when exposed to titanium dioxide in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

## **Acute Toxicity Values**

The acute effects of this product have not been tested. Data on individual components are tabulated below

CAS-No.	Chemical Name	Oral LD50	Dermal LD50	Vapor LC50
1330-20-7	XYLENE MIXTURE OF ISOMERS	Rat - 4300 mg/kg	Rabbit - >1700 mg/kg	N.I.
7429-90-5	ALUMINUM	Rat - >2000 mg/kg	N.I.	Rat - 4 hr - >888 mg/l
616-38-6	DIMETHYL CARBONATE	Rat - > 13000 mg/kg	Rabbit - > 5000 mg/kg	j N.I.
13463-67-7	TITANIUM DIOXIDE	>10000 mg/kg	>10000 mg/kg	N.I.
107-98-2	1-METHOXY-2-PROPANOL	Mouse - 11700 mg/kg	Rabbit - 13000 mg/kg	N.I.
25068-38-6	BISPHENOL A (EPICHLOROHYDRIN) EPOXY RESIN	Rat - 11400 mg/kg	Rat - 2000 mg/kg	Rat - male - 0.00001 ppm
64742-95-6	AROMATIC HYDROCARBON	>2000 mg/kg	>2000 mg/kg	N.I.
100-41-4	ETHYL BENZENE	Rat - 3500 mg/kg	Rabbit - 15433 mg/kg	N.I.
2530-83-8	GLYCIDOXYPROPYL TRIMETHOXYSILANE	Rat - 7.5 ml/kg	Rabbit - 3.97 ml/kg	N.I.
14808-60-7	CRYSTALLINE SILICA, QUARTZ	Rat - >22500 mg/kg	N.I.	N.I.

N.I. = No Information

# 12. Ecological Information

ECOLOGICAL INFORMATION: No information on ecology is available.

# 13. Disposal Information



Product

PESTICIDE DISPOSAL: No Information

CONTAINER DISPOSAL: No Information

DISPOSAL METHOD: Dispose of material in accordance with applicable federal, state and local regulations.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Dike to prevent entering any sewer or waterway. Transfer liquid to a holding container. Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust. Remove all sources of ignition, ventilate area and remove with inert absorbent and non-sparking tools. Dispose of according to local, state, and federal regulations. Do not incinerate closed containers. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Ventilate area, isolate spilled material, and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

# 14. Transport Information

SPECIAL TRANSPORT PRECAUTIONS: No special transport precautions are necessary.

	Domestic (USDOT)	International (IMDG)	Air (IATA)
UN Number:	1263	1263	1263
Proper Shipping Name:	Paint	Paint	Paint
Hazard Class:	3	3	3
Packing Group	11	11	II, Cargo Aircraft Only, if >5 L to 60 L Max
Limited Quantity:	No	Yes	No, 1 L per pkg

#### Product: 3230SP0901A

# 15. Regulatory Information

# **U.S. Federal Regulations:**

## U.S. PESTICIDE LAW

EPA STATEMENT: This product is not classified as a Pesticide by the United States Environmental Protection Agency.

EPA PESTICIDE LABEL: No Information

#### CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Flammable (gases, aerosols, liquids, or solids), Carcinogenicity, Acute Toxicity (any route of exposure), Reproductive toxicity, Skin Corrosion or Irritation, Respiratory or Skin Sensitization, Germ cell mutagenicity

#### SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

<u>Chemical Name</u>	<u>CAS-No.</u>
XYLENE MIXTURE OF ISOMERS	1330-20-7
ALUMINUM	7429-90-5
ETHYL BENZENE	100-41-4
METHYL BENZENE	108-88-3
METHANOL	67-56-1
CUMENE	98-82-8
2-PENTANONE, 4-METHYL;HEXANONE	108-10-1

## TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA components exist in this product.

# U.S. State Regulations: NEW JERSEY RIGHT-TO-KNOW:

The following materials are non-hazardous, but are among the top five components in this product.

Chemical Name	<u>CAS-No.</u>
HYDROUS MAGNESIUM SILICATE	14807-96-6

## PENNSYLVANIA RIGHT-TO-KNOW

The following non-hazardous ingredients are present in the product at greater than 3%.

<u>Chemical Name</u>	<u>CAS-No.</u>
HYDROUS MAGNESIUM SILICATE	14807-96-6

## **CALIFORNIA PROPOSITION 65 CARCINOGENS**

Warning: The following ingredients present in the product are known to the state of California to cause Cancer.

Chemical Name	CAS-No.
HYDROUS MAGNESIUM SILICATE	14807-96-6
TITANIUM DIOXIDE	13463-67-7
BISPHENOL A (EPICHLOROHYDRIN) EPOXY RESIN	25068-38-6
ETHYL BENZENE	100-41-4
CRYSTALLINE SILICA, QUARTZ	14808-60-7
CUMENE	98-82-8

# CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

<u>Chemical Name</u>	
GLYCIDOXYPROPYL TRIMETHOXYSILANE	
METHANOL	

CAS-No. 2530-83-8 67-56-1

# International Regulations: As follows -

## **CANADIAN WHMIS:**

This SDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

WHMIS Class B2,D2A

16. Othe	er Informati	on						
Revision Da	ate:	2/23/2023	2/23/2023 Supersedes Da		persedes Date:	2/6/2023		
Reason for	revision:		Substance and/or Product Properties Changed in Section(s): 09 - Physical & Chemical Information					
Datasheet	produced by:	Regulatory	Regulatory Department					
HMIS Ratings:								
Health:	2	Flammability:	1	Reactivity:	0	Personal Protection:	J	

## Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H340	May cause genetic defects.
H350	May cause cancer.
H351	Suspected of causing cancer. Classified as Category 2 based on limited evidence on human and/or animal studies. Mixtures with concentrations of suspected carcinogens ingredients at concentration present between 0.1% and 1.0% labelling the SDS will be optional depending on authorities. If Category 2 carcinogenic present at a concentration of 1% or above labelling the SDS will be expected. Routes of exposure are dependent on ingredient form.
H360	May damage fertility or the unborn child.
H361	Suspected of damaging fertility or the unborn child. Classifed Category 2 suspected human reproductive toxicant irreversible effects such as structural malfunctions, embryo/foetal lethality, post natal functional deficiencies.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs (hematopoietic system [blood forming], blood, bone marrow, immune system) through prolonged or repeated exposure.

Icons for GHS Pictograms shown in Section 3 describing each ingredient:





Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product where instructions and recommendations are not followed.