

# Safety Data Sheet

Date Printed: 3/20/2023 Product: 3020SP0025

## 1. Identification

Product Information: 3020SP0025

Product Name: SEAJET PELLERCLEAN CLEAR COAT

Recommended Use: FOUL RELEASE COATING

Supplied by: CMP Coatings, Inc. 1610 Engineers Rd.

Belle Chasse, LA 70037

Emergency Telephone: Chemtrec 24 Hour Emergency Hotline: 800-424-9300

Safety Data Sheet Coordinator: SDS@cmpusa.com

# 2. Hazards Identification

EMERGENCY OVERVIEW: Extremely Flammable!Eye irritant.

#### **GHS Classification**

Flam. Liq. 2

Symbol(s) of Product



## Signal Word

Danger

# Possible Hazards

11% of the mixture consists of ingredients of unknown acute toxicity

#### **GHS HAZARD STATEMENTS**

Flammable Liquid, category 2 H225 Highly flammable liquid and vapour.

#### **GHS LABEL PRECAUTIONARY STATEMENTS**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P233 Keep container tightly closed.

#### **GHS SDS PRECAUTIONARY STATEMENTS**

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/.../ equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

# 3. Composition/Information on Ingredients

**GHS Statements** Chemical Name CAS-No. Wt. % GHS Symbols **VINYLOXIMESILANE PROPRIETARY** 2.5-10 No Information No Information 2.5-10 GHS07 H336 N-BUTYL ACETATE 123-86-4 METHYLTRI(METHYLETHYLKETOXIME) SILANE 22984-54-9 1.0-2.5 No Information No Information ETHYL CYCLOHEXANE 1678-91-7 1.0-2.5 GHS08 H304 **ALKOXYSILANE** PROPRIETARY 0.1-1.0 No Information No Information

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

## 4. First-aid Measures



FIRST AID - INHALATION: If inhaled, remove to fresh air. Administer oxygen if necessary. Consult a physician if symptoms persist or exposure was severe.

FIRST AID - SKIN CONTACT: In case of contact, wash skin immediately with soap and water. Launder clothing before reuse. Destroy contaminated leather articles.

FIRST AID - EYE CONTACT: If material gets into eyes, flush with water immediately for 15 minutes. Consult a physician.

**FIRST AID - INGESTION:** If ingested, DO NOT induce vomiting. If conscious, drink 8-10 oz. of water promptly. Call a physician immediately.

# 5. Fire-fighting Measures

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Flammable liquid. Vapors can form an ignitable mixture with air. Vapors can flow along surfaces to a distant ignition source and flash back.

**SPECIAL FIREFIGHTING PROCEDURES:** Use a self-contained breathing apparatus with full facepiece operated in pressure-demand or other positive pressure mode. Flammable. Cool fire-exposed containers using water spray.

EXTINGUISHING MEDIA: Alcohol Foam, Carbon Dioxide, Dry Chemical, Foam, Water Fog

# 6. Accidental Release Measures

**ENVIRONMENTAL PRECAUTIONS:** Contain any spills immediately and dike area to prevent spreading. Package material and dispose of as hazardous waste.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Dike to prevent entering any sewer or waterway. Transfer liquid to a holding container. Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust. Remove all sources of ignition, ventilate area and remove with inert absorbent and non-sparking tools. Dispose of according to local, state, and federal regulations. Do not incinerate closed containers. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Ventilate area, isolate spilled material, and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

## 7. Handling and Storage





**HANDLING:** Flammable liquid. Avoid heat, sparks and open flames. Avoid breathing vapor and contact with eyes, skin and clothing. Hazardous residue may remain in emptied container. Do not reuse empty containers without commercial cleaning or reconditioning. Material will accumulate static charges which may cause an electrical spark (ignition source). Use proper grounding procedures.

STORAGE: Keep container closed when not in use.

# 8. Exposure Controls/Personal Protection

Ingredients with Occupational Exposure Limits

| Chemical Name                 | ACGIH TLV-TWA | ACGIH-TLV STEL | OSHA PEL-TWA | OSHA PEL-CEILING |
|-------------------------------|---------------|----------------|--------------|------------------|
| VINYLOXIMESILANE              | N.E.          | N.E.           | N.E.         | N.E.             |
| N-BUTYL ACETATE               | 150 ppm       | 200 ppm        | 150 ppm      | N.E.             |
| METHYLTRI(METHYLETHYLKETOXIME | ) N.E.        | N.E.           | N.E.         | N.E.             |
| SILANE `                      | ,             |                |              |                  |
| ETHYL CYCLOHEXANE             | N.E.          | N.E.           | N.E.         | N.E.             |
| ALKOXYSILANE                  | N.E.          | N.E.           | N.E.         | N.E.             |

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation Sk = Skin Sensitizer N.E. = Not Established

#### **Personal Protection**



**RESPIRATORY PROTECTION:** Respirator use is not expected to be necessary under normal conditions of handling. In emergency situations, use of a NIOSH-approved respirator may be required. When concentrations exceed the exposure limits specified, use of a NIOSH-approved dust, mist and fume respirator is recommended. Where the protection factor of the respirator may be exceeded, use of a full facepiece, supplied air, or Self Contained Breathing Apparatus (SCBA) may be necessary.



SKIN PROTECTION: Chemical-resistant gloves may be required for individuals with sensitive skin.



**EYE PROTECTION:** Ensure that eyewash stations and safety showers are close to the workstation location. Chemical resistant goggles must be worn.



**OTHER PROTECTIVE EQUIPMENT:** Use personal protective equipment as necessary. Safety shower and eyewash station should be located in immediate work area.



**HYGIENIC PRACTICES:** Contaminated clothing should be changed and washed before reuse. Eating, drinking and smoking in immediate work area should be prohibited. Keep away from food, drink and animal feeding stuffs.

water:

# 9. Physical and Chemical Properties

Appearance: Paint Physical State: Liquid

Odor Threshold: Odor: Solvent Not Established Density, g/cm3: pH: 1.012 Not Applicable Freeze Point, °F: Viscosity: No Information No Information Partition Coefficient, n-octanol/ Solubility in Water: Not Measured Insoluble

**Decomposition temperature, °F** Not Measured

Boiling Range, °F:259 - 1,472Explosive Limits, %:1.0 - 6.6Combustibility:Supports CombustionFlash Point, °F:64

Evaporation Rate: Slower than Diethyl Ether Auto-Ignition Temperature, °F Not Measured Vapor Density: Heavier than Air Vapor Pressure, mmHg: Not Measured

(See "Other information" Section for abbreviation legend)

# 10. Stability and Reactivity

**STABILITY:** Stable under recommended storage conditions.

CONDITIONS TO AVOID: Heat, flames and sparks. Extremes of temperature and direct sunlight.

**INCOMPATIBILITY:** Keep away from strong oxidizing agents, heat and open flames.

HAZARDOUS DECOMPOSITION PRODUCTS: Incomplete combustion may produce carbon monoxide and other toxic gases.

# 11. Toxicological Information



## Practical Experiences

**EFFECT OF OVEREXPOSURE - INHALATION:** Inhalation may cause mild irritation to the respiratory tract (nose, mouth, mucous membranes). Inhalation of high concentrations may cause headache, nausea, and dizziness.

**EFFECT OF OVEREXPOSURE - SKIN CONTACT:** Prolonged and repeated skin contact may cause irritation and possibly dermatitis. Prolonged and repeated skin contact may cause dermatitis, drying and defatting due to the solvent properties.

EFFECT OF OVEREXPOSURE - EYE CONTACT: Mist and vapors may cause eye irritation.

EFFECT OF OVEREXPOSURE - INGESTION: Harmful if swallowed. May cause nausea, vomiting, and diarrhea.

**CARCINOGENICITY:** This product may contain Titanium Dioxide, which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence of carcinogenicity in humans and sufficient evidence in experimental animals. This classification is relevant when exposed to titanium dioxide in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Contact

# **Acute Toxicity Values**

The acute effects of this product have not been tested. Data on individual components are tabulated below

<u>CAS-No.</u> <u>Chemical Name</u> <u>Oral LD50</u> <u>Dermal LD50</u> <u>Vapor LC50</u>

123-86-4 N-BUTYL ACETATE Rat - 10760 mg/kg Rabbit - >14112 mg/ N.I.

kg

PROPRIETA ALKOXYSILANE Rat - 2995 mg/kg Rab - 2000 mg/kg Rat - 4 hr - 1.49-2.44 mg/l

RY

N.I. = No Information

# 12. Ecological Information

ECOLOGICAL INFORMATION: No information on ecology is available.

# 13. Disposal Information



#### **Product**

PESTICIDE DISPOSAL: No Information
CONTAINER DISPOSAL: No Information

DISPOSAL METHOD: Dispose of material in accordance with applicable federal, state and local regulations.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Dike to prevent entering any sewer or waterway. Transfer liquid to a holding container. Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust. Remove all sources of ignition, ventilate area and remove with inert absorbent and non-sparking tools. Dispose of according to local, state, and federal regulations. Do not incinerate closed containers. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Ventilate area, isolate spilled material, and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

## 14. Transport Information

SPECIAL TRANSPORT PRECAUTIONS: No special transport precautions are necessary.

|                       | Domestic (USDOT) | International (IMDG) | Air (IATA)                                   |
|-----------------------|------------------|----------------------|--|
| UN Number:            | 1263             | 1263                 | 1263   |
| Proper Shipping Name: | Paint            | Paint                | Paint  |
| Hazard Class:         | 3                | 3                    | 3  |
| Packing Group         | II               | II                   | II, Cargo Aircraft Only, if >5 L to 60 L Max |
| Limited Quantity:     | No               | Yes                  | No, 1 L per pkg                              |

# 15. Regulatory Information

# U.S. Federal Regulations:

#### U.S. PESTICIDE LAW

EPA STATEMENT: This product is not classified as a Pesticide by the United States Environmental Protection Agency.

**EPA PESTICIDE LABEL:** No Information

## **CERCLA - SARA Hazard Category**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Flammable (gases, aerosols, liquids, or solids)

#### **SARA SECTION 313:**

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No Sara 313 components exist in this product.

#### **TOXIC SUBSTANCES CONTROL ACT:**

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA components exist in this product.

## U.S. State Regulations:

#### **NEW JERSEY RIGHT-TO-KNOW:**

The following materials are non-hazardous, but are among the top five components in this product.

**Chemical Name** 

NON-HAZARDOUS INGREDIENT METHYLPHENYLPOLYSILOXANE NON-HAZARDOUS INGREDIENT CAS-No.

TRADE SECRET 68083-14-7 TRADE SECRET

## PENNSYLVANIA RIGHT-TO-KNOW

The following non-hazardous ingredients are present in the product at greater than 3%.

**Chemical Name** 

NON-HAZARDOUS INGREDIENT METHYLPHENYLPOLYSILOXANE NON-HAZARDOUS INGREDIENT CAS-No.

TRADE SECRET 68083-14-7 TRADE SECRET

#### **CALIFORNIA PROPOSITION 65 CARCINOGENS**

Warning: The following ingredients present in the product are known to the state of California to cause Cancer.

No Proposition 65 Carcinogens exist in this product.

#### **CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS**

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

No Proposition 65 Reproductive Toxins exist in this product.

# International Regulations: As follows -

### **CANADIAN WHMIS:**

This SDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

WHMIS Class B2

# 16. Other Information

Revision Date: 3/20/2023 Supersedes Date: 3/20/2023

Reason for revision: Substance and/or Product Properties Changed in Section(s):

09 - Physical & Chemical Information

15 - Regulatory Information

Datasheet produced by: Regulatory Department

**HMIS Ratings:** 

Health: 2 Flammability: 1 Reactivity: 0 Personal Protection: J

## Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

## Icons for GHS Pictograms shown in Section 3 describing each ingredient:

**GHS07** 



**GHS08** 

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product where instructions and recommendations are not followed.