

1. Identification

Product Information: 3110CS0651

Product Name: SEAJET BILGE PAINT WHITE

Recommended Use: ALKYD ENAMEL

Supplied by: CMP Coatings, Inc.
1610 Engineers Rd.
Belle Chasse, LA 70037

Emergency Telephone: Chemtrec 24 Hour Emergency Hotline: 800-424-9300

Safety Data Sheet Coordinator: SDS@cmpusa.com

2. Hazards Identification

EMERGENCY OVERVIEW: FLAMMABLE liquid and vapor. COMBUSTIBLE liquid and vapor. Eye irritant.

GHS Classification

Acute Tox. 3 Inhalation, Eye Irrit. 2B, Flam. Liq. 3, Repr. 2, Skin Irrit. 2

Symbol(s) of Product



Signal Word

Danger

Possible Hazards

45% of the mixture consists of ingredients of unknown acute toxicity

GHS HAZARD STATEMENTS

Acute Toxicity, Inhalation, category 3	H331	Toxic if inhaled.
Eye Irritation, category 2B	H320	Causes eye irritation
Flammable Liquid, category 3	H226	Flammable liquid and vapour.
Reproductive Toxicity, category 2	H361	Suspected of damaging fertility or the unborn child. Classified Category 2 suspected human reproductive toxicant irreversible effects such as structural malfunctions, embryo/foetal lethality, post natal functional deficiencies.
Skin Irritation, category 2	H315	Causes skin irritation.

GHS LABEL PRECAUTIONARY STATEMENTS

P201	Obtain special instructions before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P311	Call a POISON CENTER or doctor/physician.
P362	Take off contaminated clothing.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.

GHS SDS PRECAUTIONARY STATEMENTS

P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/.../ equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.

3. Composition/Information on Ingredients

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>Wt. %</u>	<u>GHS Symbols</u>	<u>GHS Statements</u>
Petroleum naphtha	64742-48-9	10-25	GHS06-GHS08	H304-331
CALCIUM CARBONATE	1317-65-3	10-25	GHS07	H315-320-335
TITANIUM DIOXIDE	13463-67-7	10-25	GHS08	H361
STODDARD SOLVENT	8052-41-3	2.5-10	GHS08	H304
ALUMINUM HYDROXIDE	21645-51-2	0.1-1.0	No Information	No Information
ZIRCONIUM CARBOXYLATE	22464-99-9	0.1-1.0	No Information	No Information
MIXED CALCIUM CARBOXYLATES	TRADE SECRET	<0.1	No Information	No Information
DIPROPYLENE GLYCOL METHYL ETHER	34590-94-8	<0.1	No Information	No Information

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

4. First-aid Measures



FIRST AID - INHALATION: If inhaled, remove to fresh air. Administer oxygen if necessary. Consult a physician if symptoms persist or exposure was severe.

FIRST AID - SKIN CONTACT: In case of contact, wash skin immediately with soap and water. Launder clothing before reuse. Destroy contaminated leather articles.

FIRST AID - EYE CONTACT: If material gets into eyes, flush with water immediately for 15 minutes. Consult a physician.

FIRST AID - INGESTION: If ingested, DO NOT induce vomiting. If conscious, drink 8-10 oz. of water promptly. Call a physician immediately.

5. Fire-fighting Measures

UNUSUAL FIRE AND EXPLOSION HAZARDS: Flammable liquid. Vapors can form an ignitable mixture with air. Vapors can flow along surfaces to a distant ignition source and flash back.

SPECIAL FIREFIGHTING PROCEDURES: Use a self-contained breathing apparatus with full facepiece operated in pressure-demand or other positive pressure mode. Flammable. Cool fire-exposed containers using water spray.

EXTINGUISHING MEDIA: Alcohol Foam, Carbon Dioxide, Dry Chemical, Foam, Water Fog

6. Accidental Release Measures

ENVIRONMENTAL PRECAUTIONS: Contain any spills immediately and dike area to prevent spreading. Package material and dispose of as hazardous waste.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Dike to prevent entering any sewer or waterway. Transfer liquid to a holding container. Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust. Remove all sources of ignition, ventilate area and remove with inert absorbent and non-sparking tools. Dispose of according to local, state, and federal regulations. Do not incinerate closed containers. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Ventilate area, isolate spilled material, and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

7. Handling and Storage



HANDLING: Flammable liquid. Avoid heat, sparks and open flames. Avoid breathing vapor and contact with eyes, skin and clothing. Hazardous residue may remain in emptied container. Do not reuse empty containers without commercial cleaning or reconditioning. Material will accumulate static charges which may cause an electrical spark (ignition source). Use proper grounding procedures.

STORAGE: Keep container closed when not in use.

8. Exposure Controls/Personal Protection

Ingredients with Occupational Exposure Limits

<u>Chemical Name</u>	<u>ACGIH TLV-TWA</u>	<u>ACGIH-TLV STEL</u>	<u>OSHA PEL-TWA</u>	<u>OSHA PEL-CEILING</u>
Petroleum naphtha	N.E.	N.E.	N.E.	N.E.
CALCIUM CARBONATE	N.E.	N.E.	15 mg/m3 total dust, 5 mg/m3 respirable fraction	N.E.
TITANIUM DIOXIDE	10 mg/m3	N.E.	15 mg/m3	N.E.
STODDARD SOLVENT	100 ppm - 8 hrs	N.E.	500 ppm - 8 hrs	N.E.
ALUMINUM HYDROXIDE	1 mg/m3	N.E.	N.E.	N.E.
ZIRCONIUM CARBOXYLATE	5 mg/m3 as Zr	10 mg/m3 as Zr	5 mg/m3 as Zr	N.E.
MIXED CALCIUM CARBOXYLATES	N.E.	N.E.	N.E.	N.E.
DIPROPYLENE GLYCOL METHYL ETHER	100 ppm	150 ppm	100 ppm	N.E.

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation
Sk = Skin Sensitizer N.E. = Not Established

Personal Protection



RESPIRATORY PROTECTION: Respirator use is not expected to be necessary under normal conditions of handling. In emergency situations, use of a NIOSH-approved respirator may be required. When concentrations exceed the exposure limits specified, use of a NIOSH-approved dust, mist and fume respirator is recommended. Where the protection factor of the respirator may be exceeded, use of a full facepiece, supplied air, or Self Contained Breathing Apparatus (SCBA) may be necessary.



SKIN PROTECTION: Chemical-resistant gloves may be required for individuals with sensitive skin.



EYE PROTECTION: Ensure that eyewash stations and safety showers are close to the workstation location. Chemical resistant goggles must be worn.



OTHER PROTECTIVE EQUIPMENT: Use personal protective equipment as necessary. Safety shower and eyewash station should be located in immediate work area.



HYGIENIC PRACTICES: Contaminated clothing should be changed and washed before reuse. Eating, drinking and smoking in immediate work area should be prohibited. Keep away from food, drink and animal feeding stuffs.

9. Physical and Chemical Properties

Appearance:	Paint	Physical State:	Liquid
Odor:	Solvent	Odor Threshold:	Not Established
Density, g/cm³:	1.264	pH:	Not Applicable
Freeze Point, °F:	No Information	Viscosity:	No Information
Solubility in Water:	Insoluble	Partition Coefficient, n-octanol/water:	Not Measured
Decomposition temperature, °F	Not Measured		
Boiling Range, °F:	140 - 617	Explosive Limits, %:	0.7 - 21.2
Combustibility:	Supports Combustion	Flash Point, °F:	90
Evaporation Rate:	Slower than Diethyl Ether	Auto-Ignition Temperature, °F	Not Measured
Vapor Density:	Heavier than Air	Vapor Pressure, mmHg:	Not Measured

(See "Other information" Section for abbreviation legend)

10. Stability and Reactivity

STABILITY: Stable under recommended storage conditions.

CONDITIONS TO AVOID: Heat, flames and sparks. Extremes of temperature and direct sunlight.

INCOMPATIBILITY: Keep away from strong oxidizing agents, heat and open flames.

HAZARDOUS DECOMPOSITION PRODUCTS: Incomplete combustion may produce carbon monoxide and other toxic gases.

11. Toxicological Information



Practical Experiences

EFFECT OF OVEREXPOSURE - INHALATION: Inhalation may cause mild irritation to the respiratory tract (nose, mouth, mucous membranes). Inhalation of high concentrations may cause headache, nausea, and dizziness.

EFFECT OF OVEREXPOSURE - SKIN CONTACT: Prolonged and repeated skin contact may cause irritation and possibly dermatitis. Prolonged and repeated skin contact may cause dermatitis, drying and defatting due to the solvent properties.

EFFECT OF OVEREXPOSURE - EYE CONTACT: Mist and vapors may cause eye irritation.

EFFECT OF OVEREXPOSURE - INGESTION: Harmful if swallowed. May cause nausea, vomiting, and diarrhea.

CARCINOGENICITY: This product may contain Titanium Dioxide, which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence of carcinogenicity in humans and sufficient evidence in experimental animals. This classification is relevant when exposed to titanium dioxide in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>
64742-48-9	Petroleum naphtha	Rat - >5000 mg/kg	Rat - >5000 mg/kg	Rat - 4 hr - 4.95 mg/l
13463-67-7	TITANIUM DIOXIDE	>10000 mg/kg	>10000 mg/kg	N.I.
21645-51-2	ALUMINUM HYDROXIDE	Rat - > 5000 mg/kg	N.I.	N.I.
34590-94-8	DIPROPYLENE GLYCOL METHYL ETHER	Rat - 5152 mg/kg	N.I.	N.I.

N.I. = No Information

12. Ecological Information

ECOLOGICAL INFORMATION: No information on ecology is available.

13. Disposal Information



Product

PESTICIDE DISPOSAL: No Information

CONTAINER DISPOSAL: No Information

DISPOSAL METHOD: Dispose of material in accordance with applicable federal, state and local regulations.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Dike to prevent entering any sewer or waterway. Transfer liquid to a holding container. Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust. Remove all sources of ignition, ventilate area and remove with inert absorbent and non-sparking tools. Dispose of according to local, state, and federal regulations. Do not incinerate closed containers. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Ventilate area, isolate spilled material, and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

14. Transport Information

SPECIAL TRANSPORT PRECAUTIONS: No special transport precautions are necessary.

	Domestic (USDOT)	International (IMDG)	Air (IATA)
UN Number:	1263	1263	1263
Proper Shipping Name:	Paint	Paint	Paint
Hazard Class:	3	3	3
Packing Group	III	III	III
Limited Quantity:	No	Yes	Yes, 10 L per pkg

15. Regulatory Information

U.S. Federal Regulations:

U.S. PESTICIDE LAW

EPA STATEMENT: This product is not classified as a Pesticide by the United States Environmental Protection Agency.

EPA PESTICIDE LABEL: No Information

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Flammable (gases, aerosols, liquids, or solids), Acute Toxicity (any route of exposure), Reproductive toxicity, Skin Corrosion or Irritation

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

Chemical Name

PSEUDOCUMENE
DIETHYLENE GLYCOL MONOBUTYL ETHER
XYLENE MIXTURE OF ISOMERS
METHANOL
2-PENTANONE, 4-METHYL;HEXANONE

CAS-No.

95-63-6
112-34-5
1330-20-7
67-56-1
108-10-1

TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA components exist in this product.

U.S. State Regulations:**NEW JERSEY RIGHT-TO-KNOW:**

The following materials are non-hazardous, but are among the top five components in this product.

<u>Chemical Name</u>	<u>CAS-No.</u>
MODIFIED POLYESTER	63148-69-6

PENNSYLVANIA RIGHT-TO-KNOW

The following non-hazardous ingredients are present in the product at greater than 3%.

<u>Chemical Name</u>	<u>CAS-No.</u>
MODIFIED POLYESTER	63148-69-6

CALIFORNIA PROPOSITION 65 CARCINOGENS

Warning: The following ingredients present in the product are known to the state of California to cause Cancer.

<u>Chemical Name</u>	<u>CAS-No.</u>
TITANIUM DIOXIDE	13463-67-7
CRYSTALLINE SILICA, QUARTZ	14808-60-7

CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

<u>Chemical Name</u>	<u>CAS-No.</u>
METHANOL	67-56-1

International Regulations: As follows -**CANADIAN WHMIS:**

This SDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

WHMIS Class B2,D1B,D2B

16. Other Information

Revision Date:	6/16/2023	Supersedes Date:	New MSDS
Reason for revision:	No Information		
Datasheet produced by:	Regulatory Department		

HMIS Ratings:

Health:	2	Flammability:	1	Reactivity:	0	Personal Protection:	J
---------	---	---------------	---	-------------	---	----------------------	---

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H320	Causes eye irritation
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H361	Suspected of damaging fertility or the unborn child. Classified Category 2 suspected human reproductive toxicant irreversible effects such as structural malfunctions, embryo/foetal lethality, post natal functional deficiencies.

Icons for GHS Pictograms shown in Section 3 describing each ingredient:

GHS06



GHS07



GHS08



Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product where instructions and recommendations are not followed.

1. Identification

Product Information: 3110CS0614

Product Name: SEAJET BILGE PAINT LIGHT GREY

Recommended Use: Alkyd Enamel

Supplied by: CMP Coatings, Inc.
1610 Engineers Rd.
Belle Chasse, LA 70037

Emergency Telephone: Chemtrec 24 Hour Emergency Hotline: 800-424-9300

Safety Data Sheet Coordinator: SDS@cmpusa.com

2. Hazards Identification

EMERGENCY OVERVIEW: FLAMMABLE liquid and vapor. COMBUSTIBLE liquid and vapor. Eye irritant.

GHS Classification

Acute Tox. 3 Inhalation, Carc. 1A, Eye Irrit. 2B, Flam. Liq. 3, Repr. 2, Skin Irrit. 2, STOT SE 3 RTI

Symbol(s) of Product



Signal Word

Danger

Possible Hazards

42% of the mixture consists of ingredients of unknown acute toxicity

GHS HAZARD STATEMENTS

Acute Toxicity, Inhalation, category 3	H331	Toxic if inhaled.
Carcinogenicity, category 1A	H350	May cause cancer. Classified as carcinogenic Category 1 on the basis of epidemiological and/or animal data. Mixtures are classified as carcinogenic when at least 1 ingredient has been classified as carcinogenic and is present at 0.1% or above. Routes of exposure are dependant on ingredient form. May cause cancer.
Eye Irritation, category 2B	H320	Causes eye irritation
Flammable Liquid, category 3	H226	Flammable liquid and vapour.
Reproductive Toxicity, category 2	H361	Suspected of damaging fertility or the unborn child. Classified Category 2 suspected human reproductive toxicant irreversible effects such as structural malfunctions, embryo/foetal lethality, post natal functional deficiencies.
STOT, single exposure, category 3, RTI	H335	May cause respiratory irritation.
Skin Irritation, category 2	H315	Causes skin irritation.

GHS LABEL PRECAUTIONARY STATEMENTS

P201	Obtain special instructions before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P235	Keep cool.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.

P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P311	Call a POISON CENTER or doctor/physician.
P362	Take off contaminated clothing.
P370+P378	In case of fire: Use appropriate method to extinguish.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

GHS SDS PRECAUTIONARY STATEMENTS

P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/.../ equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.

3. Composition/Information on Ingredients

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>Wt. %</u>	<u>GHS Symbols</u>	<u>GHS Statements</u>
CALCIUM CARBONATE	1317-65-3	25-50	GHS07	H315-320-335
Petroleum naphtha	64742-48-9	10-25	GHS06-GHS08	H304-331
STODDARD SOLVENT	8052-41-3	10-25	GHS08	H304
TITANIUM DIOXIDE	13463-67-7	2.5-10	GHS08	H361
ZIRCONIUM CARBOXYLATE	22464-99-9	0.1-1.0	No Information	No Information
CRYSTALLINE SILICA, QUARTZ	14808-60-7	0.1-1.0	GHS08	H350-372
ALUMINUM HYDROXIDE	21645-51-2	0.1-1.0	No Information	No Information
MIXED CALCIUM CARBOXYLATES	TRADE SECRET	<0.1	No Information	No Information
DIPROPYLENE GLYCOL METHYL ETHER	34590-94-8	<0.1	No Information	No Information

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

4. First-aid Measures

FIRST AID - INHALATION: If inhaled, remove to fresh air. Administer oxygen if necessary. Consult a physician if symptoms persist or exposure was severe.

FIRST AID - SKIN CONTACT: In case of contact, wash skin immediately with soap and water. Launder clothing before reuse. Destroy contaminated leather articles.

FIRST AID - EYE CONTACT: If material gets into eyes, flush with water immediately for 15 minutes. Consult a physician.

FIRST AID - INGESTION: If ingested, DO NOT induce vomiting. If conscious, drink 8-10 oz. of water promptly. Call a physician immediately.

5. Fire-fighting Measures

UNUSUAL FIRE AND EXPLOSION HAZARDS: Flammable liquid. Vapors can form an ignitable mixture with air. Vapors can flow along surfaces to a distant ignition source and flash back.

SPECIAL FIREFIGHTING PROCEDURES: Use a self-contained breathing apparatus with full facepiece operated in pressure-demand or other positive pressure mode. Flammable. Cool fire-exposed containers using water spray.

EXTINGUISHING MEDIA: Alcohol Foam, Carbon Dioxide, Dry Chemical, Foam, Water Fog

6. Accidental Release Measures

ENVIRONMENTAL PRECAUTIONS: Contain any spills immediately and dike area to prevent spreading. Package material and dispose of as hazardous waste.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Dike to prevent entering any sewer or waterway. Transfer liquid to a holding container. Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust. Remove all sources of ignition, ventilate area and remove with inert absorbent and non-sparking tools. Dispose of according to local, state, and federal regulations. Do not incinerate closed containers. Isolate the hazard area and deny entry to unnecessary and

unprotected personnel. Ventilate area, isolate spilled material, and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

7. Handling and Storage



HANDLING: Flammable liquid. Avoid heat, sparks and open flames. Avoid breathing vapor and contact with eyes, skin and clothing. Hazardous residue may remain in emptied container. Do not reuse empty containers without commercial cleaning or reconditioning. Material will accumulate static charges which may cause an electrical spark (ignition source). Use proper grounding procedures.

STORAGE: Keep container closed when not in use.

8. Exposure Controls/Personal Protection

Ingredients with Occupational Exposure Limits

<u>Chemical Name</u>	<u>ACGIH TLV-TWA</u>	<u>ACGIH-TLV STEL</u>	<u>OSHA PEL-TWA</u>	<u>OSHA PEL-CEILING</u>
CALCIUM CARBONATE	N.E.	N.E.	15 mg/m3 total dust, 5 mg/m3 respirable fraction	N.E.
Petroleum naphtha	N.E.	N.E.	N.E.	N.E.
STODDARD SOLVENT	100 ppm - 8 hrs	N.E.	500 ppm - 8 hrs	N.E.
TITANIUM DIOXIDE	10 mg/m3	N.E.	15 mg/m3	N.E.
ZIRCONIUM CARBOXYLATE	5 mg/m3 as Zr	10 mg/m3 as Zr	5 mg/m3 as Zr	N.E.
CRYSTALLINE SILICA, QUARTZ	8 hr - 0.025 mg/m3	N.E.	8 hr - 10 mg/m3 / % Silica + 2	N.E.
ALUMINUM HYDROXIDE	1 mg/m3	N.E.	N.E.	N.E.
MIXED CALCIUM CARBOXYLATES	N.E.	N.E.	N.E.	N.E.
DIPROPYLENE GLYCOL METHYL ETHER	100 ppm	150 ppm	100 ppm	N.E.

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation
Sk = Skin Sensitizer N.E. = Not Established

Personal Protection



RESPIRATORY PROTECTION: Respirator use is not expected to be necessary under normal conditions of handling. In emergency situations, use of a NIOSH-approved respirator may be required. When concentrations exceed the exposure limits specified, use of a NIOSH-approved dust, mist and fume respirator is recommended. Where the protection factor of the respirator may be exceeded, use of a full facepiece, supplied air, or Self Contained Breathing Apparatus (SCBA) may be necessary.



SKIN PROTECTION: Chemical-resistant gloves may be required for individuals with sensitive skin.



EYE PROTECTION: Ensure that eyewash stations and safety showers are close to the workstation location. Chemical resistant goggles must be worn.



OTHER PROTECTIVE EQUIPMENT: Use personal protective equipment as necessary. Safety shower and eyewash station should be located in immediate work area.



HYGIENIC PRACTICES: Contaminated clothing should be changed and washed before reuse. Eating, drinking and smoking in immediate work area should be prohibited. Keep away from food, drink and animal feeding stuffs.

9. Physical and Chemical Properties

Appearance:	Paint	Physical State:	Liquid
Odor:	Solvent	Odor Threshold:	Not Established
Density, g/cm³:	1.195	pH:	Not Applicable
Freeze Point, °F:	No Information	Viscosity:	No Information
Solubility in Water:	Insoluble	Partition Coefficient, n-octanol/water:	Not Measured
Decomposition temperature, °F	Not Measured		
Boiling Range, °F:	140 - 617	Explosive Limits, %:	0.7 - 21.2
Combustibility:	Supports Combustion	Flash Point, °F:	90
Evaporation Rate:	Slower than Diethyl Ether	Auto-Ignition Temperature, °F	Not Measured
Vapor Density:	Heavier than Air	Vapor Pressure, mmHg:	Not Measured

(See "Other information" Section for abbreviation legend)

10. Stability and Reactivity

STABILITY: Stable under recommended storage conditions.

CONDITIONS TO AVOID: Heat, flames and sparks. Extremes of temperature and direct sunlight.

INCOMPATIBILITY: Keep away from strong oxidizing agents, heat and open flames.

HAZARDOUS DECOMPOSITION PRODUCTS: Incomplete combustion may produce carbon monoxide and other toxic gases.

11. Toxicological Information



Practical Experiences

EFFECT OF OVEREXPOSURE - INHALATION: Inhalation may cause mild irritation to the respiratory tract (nose, mouth, mucous membranes). Inhalation of high concentrations may cause headache, nausea, and dizziness.

EFFECT OF OVEREXPOSURE - SKIN CONTACT: Prolonged and repeated skin contact may cause irritation and possibly dermatitis. Prolonged and repeated skin contact may cause dermatitis, drying and defatting due to the solvent properties.

EFFECT OF OVEREXPOSURE - EYE CONTACT: Mist and vapors may cause eye irritation.

EFFECT OF OVEREXPOSURE - INGESTION: Harmful if swallowed. May cause nausea, vomiting, and diarrhea.

CARCINOGENICITY: This product contains a chemical that the International Agency for Research on Cancer (IARC) has concluded is carcinogenic to humans (Group 1). This product may contain Titanium Dioxide, which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence of carcinogenicity in humans and sufficient evidence in experimental animals. This classification is relevant when exposed to titanium dioxide in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>
64742-48-9	Petroleum naphtha	Rat - >5000 mg/kg	Rat - >5000 mg/kg	Rat - 4 hr - 4.95 mg/l
13463-67-7	TITANIUM DIOXIDE	>10000 mg/kg	>10000 mg/kg	N.I.
14808-60-7	CRYSTALLINE SILICA, QUARTZ	Rat - >22500 mg/kg	N.I.	N.I.
21645-51-2	ALUMINUM HYDROXIDE	Rat - > 5000 mg/kg	N.I.	N.I.
34590-94-8	DIPROPYLENE GLYCOL METHYL ETHER	Rat - 5152 mg/kg	N.I.	N.I.

N.I. = No Information

12. Ecological Information

ECOLOGICAL INFORMATION: No information on ecology is available.

13. Disposal Information



Product

PESTICIDE DISPOSAL: No Information

CONTAINER DISPOSAL: No Information

DISPOSAL METHOD: Dispose of material in accordance with applicable federal, state and local regulations.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Dike to prevent entering any sewer or waterway. Transfer liquid to a holding container. Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust. Remove all sources of ignition, ventilate area and remove with inert absorbent and non-sparking tools. Dispose of according to local, state, and federal regulations. Do not incinerate closed containers. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Ventilate area, isolate spilled material, and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

14. Transport Information

SPECIAL TRANSPORT PRECAUTIONS: No special transport precautions are necessary.

	Domestic (USDOT)	International (IMDG)	Air (IATA)
UN Number:	1263	1263	1263
Proper Shipping Name:	Paint	Paint	Paint
Hazard Class:	3	3	3
Packing Group	III	III	III
Limited Quantity:	No	Yes	Yes, 10 L per pkg

15. Regulatory Information

U.S. Federal Regulations:

U.S. PESTICIDE LAW

EPA STATEMENT: This product is not classified as a Pesticide by the United States Environmental Protection Agency.

EPA PESTICIDE LABEL: No Information

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Flammable (gases, aerosols, liquids, or solids), Carcinogenicity, Acute Toxicity (any route of exposure), Reproductive toxicity, Skin Corrosion or Irritation, Specific target organ toxicity (single or repeated exposure)

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

Chemical Name

PSEUDOCUMENE
XYLENE MIXTURE OF ISOMERS
ETHYL BENZENE

CAS-No.

95-63-6
1330-20-7
100-41-4

DIETHYLENE GLYCOL MONOBUTYL ETHER
METHANOL
2-PENTANONE, 4-METHYL;HEXANONE

112-34-5
67-56-1
108-10-1

TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA components exist in this product.

U.S. State Regulations:**NEW JERSEY RIGHT-TO-KNOW:**

The following materials are non-hazardous, but are among the top five components in this product.

Chemical Name
MODIFIED POLYESTER

CAS-No.
63148-69-6

PENNSYLVANIA RIGHT-TO-KNOW

The following non-hazardous ingredients are present in the product at greater than 3%.

Chemical Name
MODIFIED POLYESTER

CAS-No.
63148-69-6

CALIFORNIA PROPOSITION 65 CARCINOGENS

Warning: The following ingredients present in the product are known to the state of California to cause Cancer.

Chemical Name
TITANIUM DIOXIDE
CRYSTALLINE SILICA, QUARTZ
ETHYL BENZENE

CAS-No.
13463-67-7
14808-60-7
100-41-4

CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

Chemical Name
BENZYL BUTYL PHTHALATE
METHANOL

CAS-No.
85-68-7
67-56-1

International Regulations: As follows -**CANADIAN WHMIS:**

This SDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

WHMIS Class B2,D1B,D2A

16. Other Information

Revision Date:	3/5/2024	Supersedes Date:	6/16/2023
Reason for revision:	Substance and/or Product Properties Changed in Section(s): 01 - Product Information		
Datasheet produced by:	Regulatory Department		
HMIS Ratings:			
Health:	2	Flammability:	2
		Reactivity:	0
		Personal Protection:	J

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H320 Causes eye irritation

H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H350	May cause cancer.
H361	Suspected of damaging fertility or the unborn child. Classified Category 2 suspected human reproductive toxicant irreversible effects such as structural malfunctions, embryo/foetal lethality, post natal functional deficiencies.
H372	Causes damage to organs through prolonged or repeated exposure.

Icons for GHS Pictograms shown in Section 3 describing each ingredient:

GHS06



GHS07



GHS08



Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product where instructions and recommendations are not followed.